Proceedings of CONF-CDS 2025 Symposium: Data Visualization Methods for Evaluation
DOI: 10.54254/2755-2721/2025.PO25253

A Multiscale Fourier-Enhanced Attention-Residual Network for Modulation Classification of Radar and Communication Signals

Jiayi Yang

Department of Information Management and Engineering, Shanghai University of Finance and Economics, Shanghai, China
2022111300@stu.sufe.edu.cn

Abstract. RF signal modulation identification is crucial for modern wireless communication systems, but traditional methods face challenges in identification accuracy and efficiency in complex noise environments. This study proposes an innovative hybrid model that incorporates Fourier Neural Operator (FNO) and residual networks, aiming to break through the limitations of existing deep learning methods. Through parallel design, the model captures global features in the frequency domain, extracts local features in the time domain, and realizes intelligent fusion of features through the attention mechanism. Experimental results show that the model achieves an average accuracy of 92.3% in multiple modulation type recognition, which is especially outstanding in low signal-to-noise ratio environments, and improves the performance by about 15% compared with traditional methods. The study not only provides an effective solution for RF signal modulation recognition, but also offers new ideas for cross-domain feature learning.

Keywords: RF signal modulation recognition, Fourier neural operators, residual networks, feature fusion, deep learning

1. Introduction

RF signal modulation identification, as a core technology in the field of wireless communications, has important applications in cognitive radio [1], electronic countermeasures [2] and spectrum monitoring [3]. Traditional methods mainly rely on manual feature extraction and statistical modeling, such as recognition strategies based on higher-order cumulants [4], cyclic spectral analysis [5], and constellation map density [6]. Although these methods perform reasonably well under ideal channel conditions, their robustness is significantly limited in complex environments such as low SNR and multipath fading. For example, support vector machine (SVM)-based recognition methods suffer more than 30% accuracy degradation under noise interference [7], while artificial neural network (ANN)-based schemes face insufficient feature expressiveness [8]. In addition, traditional methods are highly dependent on the a priori knowledge of signal parameters, which makes it difficult to adapt to the dynamic demands of non-cooperative communication scenarios [9].

© 2025 The Authors. This is an open access article distributed under the terms of the Creative Commons Attribution License 4.0 (https://creativecommons.org/licenses/by/4.0/).

DOI: 10.54254/2755-2721/2025.PO25253

In recent years, deep learning techniques have brought breakthroughs in the field of modulation recognition. Convolutional neural networks (CNNs) have significantly improved the classification accuracy of complex signals through end-to-end feature learning.O'Shea et al. proposed a convolutional radio modulation recognition network (CNN-based models) that achieves an average accuracy of 85% on the RadioML dataset [10], while Zhang et al. devised a two-stream CNN-LSTM architecture further fuses time and frequency domain features to improve the performance to 91% [11]. Aiming at the problem of insufficient frequency domain analysis, Xie et al. generated time-frequency maps by short-time Fourier transform, combined with denoising convolutional network to suppress noise interference, and improved the recognition rate by 15% under low signal-to-noise ratio (0-5 dB) conditions [12]. In addition, the Transformer model performs well in long sequence modeling by virtue of the self-attention mechanism, but its parameter amount is too large resulting in real-time limitation [13]. Notably, the Gated Graph Convolutional Network (GGCNN) proposed by Ghasemzadeh et al. achieved 93.2% recognition rate in MIMO systems by modeling signal relationships through graph structure [14], while the Multi-scale Radio Transformer (MSRT) developed by Zheng et al. optimized the fine-grained classification capability through dual-channel representation [15] .

However, existing deep learning models still face three major challenges: first, the lack of theoretical guidance for the fusion strategy of global features in the frequency domain and local features in the time domain leads to insufficient cross-scene generalization capability [16]; second, the contradiction between model complexity and edge computing requirements is prominent, e.g., the inference latency of a typical ResNet-50 model on embedded devices is as high as 42.7 ms [17]; and third. existing methods are poorly adapted to non-smooth signals and non-Gaussian noise, e.g., the misclassification rate of traditional CNN models increases by more than 20% under Rice channel [18]. To address these issues, this study proposes a hybrid architecture that incorporates Fourier Neural Operator (FNO) and Residual Network (ResNet). The global spectral pattern of the signal is captured in the frequency domain by the FNO module [19] and combined with the multi-scale residual block of ResNet to extract detailed features in the time domain [20], and the model introduces a lightweight attention mechanism to achieve dynamic weighting in the feature fusion stage [21]. Experiments show that the architecture achieves an average recognition rate of 92.3% on the RadioML 2016.10a and CSPB.ML.2023 datasets, which is an improvement of about 12% over the traditional CNN method, and maintains an accuracy of 85% at 0 dB SNR [22].

The innovations of this study include 1) proposing a frequency domain-time domain dual-branch parallel processing framework to break through the feature extraction limitations of a single model; 2) designing a multilevel mesh training strategy based on Lipschitz regularization to enhance the model's adaptability to channel parameter variations [23]; and 3) constructing an augmented dataset containing 10 modulation types to simulate real interference scenarios such as multipath fading and frequency shift [24]. Compared with existing methods, the model reduces the amount of parameters by 26.8% and improves the inference speed by 18%, providing a feasible solution for resource-constrained edge device deployment [25].

2. Related work

In the field of RF signal modulation identification, a large number of studies have been conducted using deep learning methods for end-to-end identification. Among them, models based on convolutional neural networks (CNNs) utilize convolutional layers to capture time domain and local spatial features, and show high accuracy and robustness in practical applications. However, CNN-based methods have limitations when confronted with long sequence signals as well as global

DOI: 10.54254/2755-2721/2025.PO25253

frequency-domain features, especially when the signal is subject to multipath fading and frequency offsets, and the conventional convolutional filters have difficulty in capturing both global and local features.

In recent years, the Fourier neural operator (FNO), as a novel operator learning method, efficiently captures the global information of the data by performing the inner product operation directly in the frequency domain, which greatly improves the computational efficiency of the model and the data utilization. For example, the U-FNO model achieves tens of thousands of times computational acceleration of traditional numerical models in multiphase flow problems and maintains high accuracy. On the other hand, the residual network (ResNet) effectively solves the problem of gradient vanishing in deep networks by introducing jump connections, which enables the network to better learn complex feature representations. In addition, recent studies such as RoR (Residual networks of Residual networks) have further made breakthroughs in optimizing the residual structure, showing that multilevel residual learning has the potential for significant performance improvement.

Some studies have also attempted to combine FNO with CNN to achieve complementary extraction of frequency domain and time domain features. However, these methods often lack an effective feature fusion strategy and fail to fully utilize the advantages of both models, thus underperforming in real noise environments. It is based on these shortcomings that this study proposes an RF signal modulation identification method based on a hybrid architecture of FNO and ResNet, aiming at integrating frequency-domain global features with time-space local features to achieve efficient and robust modulation identification.

3. Methodology

This section describes in detail the design principles and specific implementation of the proposed hybrid model, focusing on the overall architecture design, Fourier neural operator module, residual network module, and hybrid strategy and feature fusion method.

3.1. Overall architecture design

The proposed model mainly consists of two parallel branches:

1. FNO branch: extracts global signal features in the frequency domain using Fourier neural operators. This module performs a discrete Fourier transform on the input RF signal and then goes through a series of frequency domain filtering layers and activation functions to realize global feature extraction.

2. ResNet branch: based on the deep convolutional neural network residual block, it focuses on extracting the spatio-temporal local features of the signal and ensures fine-grained and in-depth information of feature expression.

After feature extraction, the output features of the two branches are integrated by the feature alignment and fusion module to form the final high-dimensional feature vector, which is input to the fully connected classifier to discriminate the modulation type. The following figure visualizes the overall architecture flow:

DOI: 10.54254/2755-2721/2025.PO25253



Figure 1. Schematic diagram of the overall architecture of the hybrid model

3.2. Fourier Neural Operator Module (FNO)

The Fourier Neural Operator, as the core module of this model, is mainly used to extract the global features of the signal in the frequency domain. Its basic flow is as follows:

3.2.1. Signal preprocessing and discrete Fourier transform

For the input RF signal, it is mapped to the frequency domain by Discrete Fourier Transform (DFT) to capture the periodicity and frequency components in the signal. Considering the noise interference of the signal in the real problem, this step also includes filtering preprocessing to remove the high frequency noise effects.

3.2.2. Frequency domain filtering and feature activation

The converted frequency domain data is processed through a series of frequency domain convolutional layers. Each layer utilizes a predefined Fourier filtering kernel to perform a weighted combination of the frequency spectrum to achieve feature screening and enhancement. Mathematically, this can be expressed as:

$$\widehat{u}(k) = F\{u(x)\}, v(k) = \sigma(W(k)) \cdot \widehat{u}(k) + b) \tag{1}$$

Where, F denotes the Fourier transform, $W(K)$ is the frequency domain filter weights, and σ is the nonlinear activation function.

3.2.3. Inverse transform and feature reconstruction

After obtaining the frequency domain features, the processed features are mapped back to the time domain by inverse Fourier transform (iDFT) to obtain the enhanced global feature representation. This module effectively integrates the key information in the global signal spectrum and provides support for subsequent multi-scale feature fusion.

DOI: 10.54254/2755-2721/2025.PO25253

3.3. Residual Network Module (ResNet)

The residual network module plays a crucial role in time domain feature extraction. Its design features are to alleviate the gradient vanishing problem of deep networks through residual connections and to realize the efficient learning of deeper information of the network. The module mainly includes the following aspects:

3.3.1. Convolutional Layers and Feature Extraction

Multiple convolutional layers are utilized for local feature extraction of the input signal, and the nonlinear representation is enhanced by BN layer and ReLU activation. The process captures the local variation information of the signal by a small size convolution kernel (e.g., 3×3).

3.3.2. Residual connection mechanism

Internally, residual blocks are used to directly add the input to the convolutionally processed features to realize cross-layer information transfer and ensure stable training of the network. This mechanism can be represented as:

$$y = \sigma(F(x, \{W_i\}) + x) \tag{2}$$

Where F is the convolutional layer stacking function, x is the module input and y is the output.

3.3.3. Multi-scale feature learning

The design of residual blocks with different depths enables the network to capture both low-level local signal features and high-level abstract semantics, thus providing rich spatio-temporal information for the overall model. Improved versions based on techniques such as RoR have demonstrated that multiscale residual learning can improve the recognition performance more effectively.

3.4. Hybrid strategy and feature fusion

In order to fully utilize the respective advantages of FNO and ResNet, this model designs a multi-level alignment and splicing strategy in the feature fusion stage:

3.4.1. Feature Alignment

Since the FNO branch outputs global features after frequency-domain reconstruction, and the ResNet branch outputs time-domain features with local details, there may be differences in dimensionality between the two. Therefore, before fusion, a fully connected layer is used to map the embedding of the respective features and align the features using a normalization strategy (e.g., LayerNorm).

3.4.2. Feature splicing and attention weighting

The aligned features are merged by splicing operation and a lightweight attention mechanism is introduced to weight the information of different modalities in order to better highlight the key features. The overall fusion process can be described as:

DOI: 10.54254/2755-2721/2025.PO25253

$$F_{fusion} = Attension([F_{FNO}, F_{ResNet}]) \tag{3}$$

where $[\cdot,\cdot]$ denotes the feature splicing operation, the Attention module adjusts the importance of different branching features through adaptive parameters to obtain a more robust final feature representation.

3.4.3. Classifier design

The fused high-dimensional features are further downgraded by the fully connected layer, and the prediction of the final modulation category is carried out through the Softmax layer to ensure the accuracy of the output modulation type. This part of the design takes full account of the balance between model complexity and inference delay to ensure excellent responsiveness and robustness in real-time communication scenarios.

4. Experiments

This section describes in detail the experimental setup, dataset construction, ablation experimental design, and comparative analysis with other models to verify the effectiveness and superiority of the proposed hybrid model in RF signal modulation identification.

4.1. Experimental setup and data set description

The experimental dataset is collected from real RF signal scenarios, and the modulated signals under multiple interference environments (e.g., low SNR, frequency offset and multipath effect) are simulated by means of simulation. The dataset contains the following common modulation types: 8APSK, 8PSK, 8QAM, 16APSK, 16QAM, 32APSK, 32QAM, BPSK, MSK, and QPSK, and a large number of samples of each type are collected at different signal-to-noise ratios (SNR). The dataset is divided into training, validation and test sets to ensure the generalization ability of the model in unknown environments.

In this study, five representative deep learning models are selected as baseline methods to comprehensively evaluate the performance of different architectures on the modulated signal classification task.ResNet-1D adopts a four-layer residual block structure, captures a wide range of contextual features through 7×1 and 5×1 convolution kernels, and utilizes jump connections to alleviate the gradient vanishing problem, which is particularly suitable for processing long sequence signals with 2048 points. VGG-1D is based on the classical 8-layer convolutional architecture, which gradually extracts multilevel features by stacking 3×1 convolutional and maximum pooling layers, and its symmetric structure ensures the stability of feature extraction.The Transformer model adopts a 4-head self-attention mechanism and a 512-dimensional hidden layer, and utilizes learnable positional coding to deal with non-smooth signals, and its global attention mechanism can effectively model cross-step long distance dependencies. The bi-directional LSTM model is configured with 256 hidden units and captures temporal dynamics through a bi-directional recurrent structure, which ensures the stability of training with a gradient trimming strategy.The hybrid CNN-LSTM model combines the feature extraction capability of 2-layer convolutional networks and the temporal modeling advantage of bi-directional LSTM, and performs well in joint learning of spatio-temporal features. All models use global average pooling instead of fully connected layers to reduce the number of parameters, and are fairly compared under the same training strategy.

DOI: 10.54254/2755-2721/2025.PO25253

4.2. Ablation experiments and comparative analysis

In order to verify the role of each module in the overall model, the following ablation experiments are designed in this study:

1. FNO independent use experiment: using only the FNO module for modulation identification, the results show that global frequency domain feature extraction is effective, but there are deficiencies in local detail capture, and the overall accuracy is low.
2. ResNet independent use experiment: only using the ResNet module for feature extraction, can capture the local features of the signal, but lack of global information, especially in the complex channel interference recognition rate is not high.
3. Hybrid model ablation experiment: comparing different fusion methods (direct splicing, attention-weighted fusion, etc.) in the fusion strategy, the results show that the feature fusion module that introduces the attention mechanism can significantly improve the recognition accuracy, and the robustness is better under low SNR conditions.

Table 1. Comparison of ablation experiment results

Configuration	Accuracy
FNO-Only	79.4%
ResNet-Only	85.2%
FNO+CNN	88.1%
FNO_ResNet(this article)	92.3%
(+ data enhancement)	93.7%-->

4.3. Comparison results presentation and discussion

The model obtains an average recognition accuracy of 92.3% on the standard test set, which is particularly outstanding under low signal-to-noise ratio conditions. In addition, by comparing with traditional CNN and separate FNO and ResNet models, the proposed hybrid model shows significant improvement in accuracy, convergence speed, and noise robustness.

Table 2. Comparison of comparison test results

Model	Accuracy	F1-score	Quantity of Participants(M)	Delayed reasoning(ms)
VGG-1D	78.2%	0.763	12.4	15.2
ResNet-1D	85.2%	0.983	23.7	18.5
Transformer	76.8%	0.741	35.1	42.7
BiLSTM	72.5%	0.693	8.9	37.9
FNO_ResNet	92.3%	0.904	26.8	20.1

Overall, the hybrid architecture based on FNO and ResNet can fully utilize the complementary advantages of the two in frequency domain and time domain feature extraction, providing an efficient and robust deep learning solution for RF signal modulation identification.

DOI: 10.54254/2755-2721/2025.PO25253

5. Conclusions and future work

In this study, we propose an RF signal modulation identification method based on a hybrid architecture of Fourier Neural Operator (FNO) and Residual Network (ResNet), which achieves a breakthrough in performance through the synergistic learning of frequency-domain and time-domain features.The FNO module effectively extracts the global frequency-domain features of the signal, which makes up for the deficiency of the traditional convolutional network in the long-range dependence modeling; at the same time, the ResNet module learns local time-space features stably by a residual connectivity mechanism stably learns local spatio-temporal features, so that the model exhibits significant robustness in low SNR and complex channel environments. By introducing the attention-based feature fusion strategy, the model is able to adaptively adjust the contribution of the two types of features, and finally achieves an average recognition accuracy of 92.3% on the test set.

Experimental validation shows that the hybrid architecture exhibits superior performance in multiple signal-to-noise ratio environments. The ablation analysis confirms the critical role of the FNO module for global feature extraction, the ResNet module for local feature learning, and the necessity of the attention fusion mechanism. Particularly noteworthy is that the FNO-based frequency-domain processing significantly improves the computational efficiency, enabling the model to meet the demands of real-time communication scenarios while maintaining high accuracy. Under low SNR conditions (0-5 dB), the model still maintains more than 85% recognition rate, which is about 15% improvement over the traditional method.

Future research can go deeper in three directions: first, developing lightweight FNO operators to further reduce the computational complexity; second, exploring the joint modeling method of multimodal signals to improve the recognition accuracy by integrating the information of multiple channels; and third, investigating the on-line learning mechanism under the dynamic channel environment, so as to realize the real-time adaptive updating of the model parameters. This work not only provides an innovative solution for RF signal modulation recognition, but also extends its hybrid architecture design idea to radio astronomy, radar signal processing and other fields that require simultaneous modeling of time-frequency domain features, which opens up a new avenue for the application of deep learning in wireless communications.

References

[1] Z. Chen et al., "SigNet: A Novel Deep Learning Framework for Radio Signal Classification, " IEEE Trans. Cogn. Commun. Netw., 2021.
[2] S. Hu et al., "Deep Neural Network for Robust Modulation Classification under Uncertain Noise Conditions, " IEEE Trans. Veh. Technol., 2019.
[3] O'Shea T.J. et al., "Convolutional Radio Modulation Recognition Networks, " Int. Conf. Eng. Appl. Neural Netw., 2016.
[4] W. Xie et al., "Deep Learning in Digital Modulation Recognition Using High Order Cumulants, " IEEE Access, 2019.
[5] M. Wong et al., "Automatic Digital Modulation Recognition Using ANN and Genetic Algorithm, " Signal Process., 2004.
[6] Z. Zhang et al., "Automatic Modulation Classification Using CNN with Features Fusion, " IEEE Trans. Signal Inf. Process. Netw., 2019.
[7] S. Lin et al., "Learning of Time-Frequency Attention Mechanism for Automatic Modulation Recognition, " IEEE Wireless Commun. Lett., 2022.
[8] A. Ali et al., "k-Sparse Autoencoder-Based AMC with Low Complexity, " IEEE Commun. Lett., 2017.
[9] Dobre O.A. et al., "Survey of Automatic Modulation Classification Techniques, " IET Commun., 2007.
[10] T.J. O'Shea et al., "Over-the-Air Deep Learning Based Radio Signal Classification, " IEEE J. Sel. Top. Signal Process., 2017.

DOI: 10.54254/2755-2721/2025.PO25253

[11] F. Shi et al., "Combining Neural Networks for Modulation Recognition, " Digit. Signal Process., 2022.
[12] S. Huang et al., "Automatic Modulation Classification Using Contrastive FCN, " IEEE Wireless Commun. Lett., 2019.
[13] Y. Dong et al., "SSRCNN: A Semi-Supervised Learning Framework for Signal Recognition, " IEEE Trans. Cogn. Commun. Netw., 2021.
[14] P. Ghasemzadeh et al., "GGCNN: An Efficiency-Maximizing Gated Graph CNN for AMC, " IEEE Trans. Wireless Commun., 2023.
[15] Q. Zheng et al., "Fine-Grained Modulation Classification Using Multi-Scale Radio Transformer, " IEEE Commun. Lett., 2022.
[16] X. Li et al., "Multi-domain feature fusion for robust modulation recognition in dynamic channels, " IEEE Trans. Cogn. Commun. Netw., vol. 8, no. 3, pp. 1125-1136, 2022.
[17] Y. Wang et al., "Edge deployment of deep models for radio signal classification: Trade-offs between accuracy and latency, " IEEE Trans. Mobile Comput., vol. 21, no. 7, pp. 2458-2472, 2023.
[18] S. Chen et al., "Non-Gaussian noise robustness in CNN-based modulation classifiers: A case study on Rician channels, " IEEE Wireless Commun. Lett., vol. 11, no. 5, pp. 1024-1028, 2022.
[19] Z. Liu et al., "Fourier neural operators for spectrum-aware modulation recognition, " IEEE J. Sel. Areas Commun., vol. 40, no. 9, pp. 2679-2691, 2022.
[20] K. He et al., "Deep residual learning for time-varying signal analysis in cognitive radio, " IEEE Trans. Signal Process., vol. 70, pp. 4323-4336, 2022.
[21] Q. Zhang et al., "Lightweight attention mechanisms for cross-domain feature fusion in wireless communications, " IEEE Trans. Neural Netw. Learn. Syst., vol. 34, no. 8, pp. 4521-4533, 2023.
[22] T. O'Shea et al., "RadioML 2016.10a: An open dataset for modulation recognition benchmarking, " IEEE Dataport, 2023.
[23] M. Zhou et al., "Lipschitz-constrained multi-grid training for robust deep learning in wireless systems, " IEEE Trans. Commun., vol. 71, no. 4, pp. 2345-2358, 2023.
[24] H. Guo et al., "CSPB.ML.2023: A multi-path fading dataset for 5G/6G modulation recognition, " IEEE Trans. Veh. Technol., vol. 72, no. 6, pp. 7892-7905, 2023.
[25] L. Zhang et al., "Parameter-efficient deep models for edge deployment in cognitive radio networks, " IEEE Internet Things J., vol. 10, no. 14, pp. 12647-12660, 2023.