Proceedings of CONF-FMCE 2025 Symposium: Semantic Communication for Media Compression and Transmission
DOI: 10.54254/2755-2721/2025.GL28750

Advancements in Photonic Integrated Circuits

Junye Liang

Tianjin University, Tianjin, China
13072234271@163.com

Abstract. Photonic integrated circuits (PICs) are a transformative technology with profound implications for communications, sensing, computing, and other fields. This paper systematically reviews recent advancements in PICs, covering their fundamental principles, design methodologies, fabrication processes, and diverse applications. A comprehensive analysis of the literature highlights key technological breakthroughs, including enhanced integration density, adoption of novel materials, and optimized fabrication techniques. These advancements have significantly improved PIC performance, establishing them as a superior solution for applications such as data center interconnects, quantum computing, and gas sensing. However, challenges such as limited integration density, high manufacturing costs, and performance optimization complexities remain. Future research aims to address these hurdles by improving integration density, reducing costs, and enhancing performance to accelerate PIC commercialization. This paper provides researchers with a comprehensive perspective to foster further innovation in PIC development.

Keywords: Photonic Integrated Circuits, Optical Communication, Integrated Photonics, Manufacturing Processes, Application Areas

1. Introduction

The rapid advancement of information technology has intensified the demand for high-speed, low-power, and high-bandwidth communication systems. Photonic Integrated Circuits (PICs) have emerged as a transformative technology, garnering significant interest due to their superior performance in applications such as communication, sensing, and computing [1]. The foundation for PIC development was established in the late 1970s with the invention of the diode laser, which enabled the creation of active photonic components [2]. In 1987, Suzuki and colleagues reported the monolithic integration of a DFB laser with an MAQ optical modulator, overcoming early challenges in combining active photonic elements [3]. In the early 2000s, research teams at Intel and Luxtera advanced silicon photonics by leveraging CMOS-compatible processes to fabricate low-loss waveguides and high-speed modulators, addressing critical barriers to scalability and cost [4]. The Integrated Photonics Systems Roadmap (IPSR-I), developed by organizations such as AIM Photonics and PhotonDelta, identified packaging costs and laser integration as primary bottlenecks, prompting innovations in hybrid indium phosphide (InP)-silicon platforms [5]. Recent work by J.E. Bowers and colleagues has expanded PIC applications to quantum computing and LIDAR, tackling challenges related to power efficiency and component density [6].

© 2026 The Authors. This is an open access article distributed under the terms of the Creative Commons Attribution License 4.0 (https://creativecommons.org/licenses/by/4.0/).

DOI: 10.54254/2755-2721/2025.GL28750

PICs offer several key advantages. Firstly, photonic signals propagate at speeds approaching that of light, providing a significant bandwidth advantage over electronic signals for high-speed data processing [7]. Secondly, photonic signals generate minimal electromagnetic interference and exhibit low crosstalk between devices, ensuring high performance stability in densely integrated systems [4]. Additionally, PICs demonstrate superior energy efficiency, as photonic devices require minimal electrical energy conversion during operation, resulting in significantly lower power consumption compared to traditional electronic integrated circuits [8]. Despite these advantages, PICs face challenges, including limitations in integration density, high manufacturing costs, and complexities in performance optimization [5]. Future research will focus on enhancing integration density, reducing costs, and improving performance to accelerate the commercial adoption of PIC technology [5].

2. Key components of PICs

PICs combine active and passive photonic components to perform complex optical functions, analogous to transistors and interconnects in electronic integrated circuits. The operation of PICs is grounded in fundamental photonic principles, such as waveguiding, which confines and directs light through high-refractive-index materials via total internal reflection. Waveguides, typically fabricated from silicon or indium phosphide, enable low-loss light propagation across the chip [9] (See Figure 1).

Active components in PICs, such as distributed feedback (DFB) lasers, produce coherent light with a stable wavelength, critical for reliable signal transmission in applications like optical telecommunications. These lasers use a grating structure within the waveguide to select a specific wavelength, ensuring high spectral purity [10]. Modulators, such as Mach-Zehnder interferometers, encode data by splitting light into two paths, altering the phase or amplitude in one path via the electro-optic effect—where an applied electric field modifies the material's refractive index—and recombining the beams to create interference patterns that represent data. This enables high-speed data encoding for applications like coherent communication systems [11]. Photodetectors, such as germanium-based photodiodes, absorb incoming light and convert it into electrical signals, leveraging germanium's compatibility with silicon processes and its strong absorption in the near-infrared spectrum used in telecom [12].

Passive components, including directional couplers, beam splitters, and arrayed waveguide gratings, manage light routing and wavelength selection. Couplers transfer light between waveguides, splitters divide optical power for parallel processing, and filters isolate specific wavelengths, enabling wavelength-division multiplexing (WDM). WDM allows multiple data streams to travel simultaneously over a single fiber, significantly boosting bandwidth for high-capacity networks like data centers and long-haul communication systems [13].

The integration of these components, exemplified by milestones such as M. Smit's pioneering work on laser-modulator integration, enables compact, high-performance systems. These systems capitalize on the high bandwidth and low latency of photons, which propagate at speeds approaching 3×10^8 m/s in a vacuum, slightly reduced in materials due to their refractive index [14].

DOI: 10.54254/2755-2721/2025.GL28750



Figure 1. A scheme of the typical photonic integrated circuit [15]

3. Materials for PICs

Material selection is critical for optimizing the optical performance, compatibility, and cost-effectiveness of PICs (Table 1). Silicon, with a high refractive index (≈3.5) and compatibility with complementary metal-oxide-semiconductor (CMOS) processes, is widely used for waveguides and passive components, achieving propagation losses of ~0.5–2 dB/cm [7]. Its ability to confine light efficiently via total internal reflection supports scalable production. However, silicon's indirect bandgap limits its use in active components like lasers. Indium phosphide (InP), with its direct bandgap, is ideal for active elements such as lasers and optical amplifiers, offering optical gains of ~10–20 dB and bandwidths of ~10–100 nm for enhanced signal strength [10]. Hybrid platforms, like those from Intel and Luxtera, integrate silicon and InP to combine passive and active functionalities [16]. Silicon nitride (SiN) provides low-loss waveguiding with propagation losses of ~0.1–0.5 dB/cm, making it suitable for passive components [17]. Lithium niobate ($LiNbO_3$) enables high-speed modulation via the electro-optic effect, supporting bandwidths of ~10–100 GHz [18]. Emerging materials like graphene are being explored for their advanced optical properties to address integration challenges noted in the Integrated Photonics Systems Roadmap, but they remain in the functional layer verification stage and lack CMOS-compatible large-area transfer [5].

Table 1. Optical and electronic properties of key PIC materials

Material	Refractive Index	Bandgap Type	Applications	CMOS Compatible
Silicon	~3.5	Indirect	Waveguides, Passive Components	Yes
Indium Phosphide	~3.2	Direct	Lasers, Amplifiers	Partial
Silicon Nitride	~2.0	Indirect	Low-Loss Waveguides	Yes
Lithium Niobate	~2.2	Indirect	High-Speed Modulators	No

4. Fabrication processes for PICs

PICs rely on advanced semiconductor manufacturing techniques tailored for high precision and scalability, often compatible with CMOS infrastructure. These processes create intricate photonic components that guide and manipulate light with minimal loss, leveraging the high-speed propagation of photons and their immunity to electromagnetic interference [19]. Lithography is a cornerstone technique, enabling the precise patterning of complex layouts for waveguides, modulators, and other optical components. This is followed by etching processes that carve these

DOI: 10.54254/2755-2721/2025.GL28750

patterns into materials like silicon or silicon nitride, forming structures designed to channel light efficiently [14]. These steps ensure the creation of high-precision optical pathways critical for PIC performance. Deposition methods, such as chemical vapor deposition (CVD), add thin layers of materials with tailored optical properties, ensuring compatibility with the circuit's design [9]. These layers are essential for controlling light propagation and enabling functionalities like modulation and detection within the PIC.

To combine the strengths of different materials, hybrid integration techniques are employed. For instance, wafer bonding and micro-transfer printing allow seamless integration of silicon, ideal for passive waveguiding, with indium phosphide (InP), which excels in active functions like optical amplification and lasing [20]. These methods enable PICs to support both passive and active functionalities on a single chip, enhancing performance and versatility.

However, packaging remains a critical challenge, particularly fiber-to-chip coupling, which connects the PIC to external optical fibers. Ongoing research focuses on developing cost-effective packaging solutions to improve scalability and reduce production costs, building on advancements in silicon photonics to make PICs more accessible for widespread applications [21].

5. Advantages and challenges of PICs

PICs provide significant advantages over traditional electronic circuits, driven by the unique properties of photons. Unlike electrons, photons travel at near-light speeds, enabling ultra-low latency and supporting data rates in the terabit-per-second range [19]. This makes PICs exceptionally well-suited for high-bandwidth applications like telecommunications, data centers, and high-performance computing, where rapid data transfer is critical [22]. PICs also reduce power consumption by minimizing the need for energy-intensive electrical-to-optical signal conversions, a common bottleneck in electronic systems [9]. Their immunity to electromagnetic interference ensures reliable operation in dense, complex environments, such as integrated computing platforms [14]. Additionally, the ability to modulate light via the electro-optic effect and amplify signals optically enhances signal efficiency and supports wide bandwidths, further boosting performance [11].

Despite these strengths, PICs face challenges that hinder their widespread adoption. Integration density is limited by optical and thermal constraints, which complicate the miniaturization of photonic components compared to electronic counterparts [21]. Manufacturing costs, particularly for hybrid integration and packaging processes like fiber-to-chip coupling, remain high, as highlighted in the Integrated Photonics Systems Roadmap [5]. These complexities, along with the need to optimize optical performance, drive ongoing research to improve scalability, reduce costs, and enhance the commercial viability of PICs for broader applications [20].

6. Applications of PICs

PICs are transformative technologies with diverse applications, leveraging their high bandwidth, low latency, and immunity to electromagnetic interference. These properties, enabled by materials like silicon and indium phosphide (InP) and advanced fabrication techniques, make PICs pivotal in fields beyond traditional telecommunications and data centers [23].

In optical telecommunications, PICs enable efficient, high-capacity data transmission over long distances with minimal signal loss. Techniques like wavelength-division multiplexing allow multiple data streams to travel simultaneously through a single optical fiber, supporting the high-bandwidth demands of internet infrastructure and 5G networks [13]. In data centers, PICs power optical

DOI: 10.54254/2755-2721/2025.GL28750

interconnects, reducing latency and energy consumption compared to electronic systems. Silicon photonics-based transceivers, for instance, enhance the efficiency of cloud computing and big data analytics by facilitating rapid data transfer [24]. PICs also excel in sensing and metrology, enabling compact, sensitive sensors for monitoring environmental factors like temperature, pressure, or chemical composition. Silicon nitride-based photonic sensors, for example, are used in gas detection and biomedical diagnostics, offering real-time, high-precision analysis for applications like environmental monitoring and healthcare diagnostics [25]. In quantum computing and communication, PICs are critical for scalable quantum photonic systems. They manipulate light at the single-photon level, enabling quantum information processing and secure communication protocols like quantum key distribution, advancing the development of quantum technologies [26]. In LIDAR and autonomous systems, PICs support compact, cost-effective optical systems for high-resolution 3D mapping and navigation. Integrated photonic beam-steering devices replace bulky mechanical components, improving reliability for autonomous vehicles and robotics [27].

Biomedical applications benefit from PICs through advanced imaging and diagnostic tools. Integrated photonic biosensors enable label-free detection of biomolecules, supporting rapid, point-of-care diagnostics in medical research and clinical settings [28]. PICs are gaining traction in artificial intelligence and machine learning, where photonic processors exploit the speed of light to perform complex computations, such as matrix operations, offering energy-efficient alternatives to electronic processors for neural network training and inference [29].

7. Conclusion

PICs are transforming technology with their high speed, bandwidth, and energy efficiency, driving advancements across telecommunications, data centers, sensing, quantum computing, LIDAR, biomedical diagnostics, and AI. By integrating active components like lasers and modulators with passive elements such as waveguides and couplers, PICs leverage the rapid propagation of photons —approaching 3×10^8 m/s—and minimal electromagnetic interference to outperform traditional electronic circuits. Breakthroughs in high-density integration, materials like silicon and indium phosphide (InP), and CMOS-compatible fabrication have significantly enhanced PIC performance and scalability, enabling applications like wavelength-division multiplexing for high-capacity networks and compact photonic sensors for real-time diagnostics.

Despite these advancements, challenges persist, including limited integration density due to optical and thermal constraints, high manufacturing costs—particularly for hybrid integration and packaging—and complexities in performance optimization. For instance, fiber-to-chip coupling remains a costly bottleneck, as noted in the Integrated Photonics Systems Roadmap. Future research will focus on novel materials like graphene, which offers advanced optical properties, and innovative fabrication techniques to improve scalability and reduce costs. Cost-effective packaging solutions are also critical to making PICs commercially viable. These advancements will empower PICs to support next-generation technologies, such as 6G networks, scalable quantum systems, compact sensors for environmental and biomedical applications, and energy-efficient photonic processors for AI. Collaborative efforts across academia and industry will accelerate PIC commercialization. By addressing these challenges, PICs will enable breakthroughs in high-speed, low-power systems. This will usher in a new era of sustainable technologies, reshaping industries and addressing global challenges. Continued innovation in PICs will ensure their pivotal role in future technological ecosystems.

DOI: 10.54254/2755-2721/2025.GL28750

References

[1] Blumenthal, D.J., Heideman, R., Geuzebroek, D., Leinse, A., and Roeloffzen, C. (2018) Silicon nitride in silicon photonics, Proc. IEEE, 106(12): 2209–2231. doi: 10.1109/JPROC.2018.2861576.

[2] Smit, M. K., & Dam, C.V. (1996) PHASAR-based WDM-devices: Principles, design and applications, IEEE J. Sel. Topics Quantum Electron., 2(2): 236–250. doi: 10.1109/2944.577370.

[3] Suzuki, A., et al. (1987) Monolithic Integration of a DFB Laser and an MAQ Optical Modulator in the 1.5-μm Wavelength Range. IEEE J. Quantum Electron., 23(6): 915–918. doi: 10.1109/JQE.1987.1073447.

[4] Jalali, B., & Fathpour, S. (2006) Silicon photonics, J. Lightw. Technol., 24(12): 4600–4615..doi: 10.1109/JLT.2006.885782.

[5] PhotonDelta. (2023) Integrated Photonics Systems Roadmap—International, PhotonDelta and MIT Microphotonics Center. https: //www.photondelta.com/downloads/

[6] Xiang, C., Jin, W., Terra, O., et al. (2023) 3D integration enables ultralow-noise isolator-free lasers in silicon photonics, Nature, 620: 78–85. 2023, doi: 10.1038/s41586-023-06251-w.

[7] Reed, G. T., & Knights, A. P. (2004) Silicon Photonics: An Introduction. Hoboken, NJ, USA: Wiley.

[8] Miller, D. A. B. (2017) Attojoule optoelectronics for low-energy information processing and communications, J. Lightw. Technol., 35(3): 346–396. doi: 10.1109/JLT.2017.2647779.

[9] Soref, R. (2006) The past, present, and future of silicon photonics, IEEE J. Sel. Topics Quantum Electron., 12(6): 1678–1687. doi: 10.1109/JSTQE.2006.883151.

[10] Coldren, L. A., Corzine, S. W., & Mashanovitch, M. L. (2012) Diode Lasers and Photonic Integrated Circuits, 2nd ed. Hoboken, NJ, USA: Wiley.

[11] Reed, G., Mashanovich, G., Gardes, F., et al. (2010) Silicon optical modulators, Nature Photon., 4: 518–526. doi: 10.1038/nphoton.2010.179.

[12] Michel, J. Liu, J., and Kimerling, J. (2010) High-performance Ge-on-Si photodetectors, Nature Photon., 4: 527–534. doi: 10.1038/nphoton.2010.157.

[13] Doerr, C. R. (2015) Silicon photonic integration in telecommunications, Front. Phys., 3(37). doi: 10.3389/fphy.2015.00037.

[14] Smit, M., van der Tol, J., & Hill, M. (2012) Moore's law in photonics, Laser Photon. Rev., 6(1): 1–13. doi: 10.1002/lpor.201100001.

[15] Osgood, R., & Meng, X. (2022) Principles of Photonic Integrated Circuits: Materials, Device Physics, Guided Wave Design. Cham, Switzerland: Springer.

[16] Heck, M. J. R., et al. (2013) Hybrid silicon photonic integrated circuit technology, IEEE J. Sel. Topics Quantum Electron., 19(4): 6100117. doi: 10.1109/JSTQE.2012.2235413.

[17] Bauters, J. F., et al. (2011) Ultra-low-loss high-aspect-ratio Si3N4 waveguides, Opt. Express, 19(4): 3163–3174. doi: 10.1364/OE.19.003163.

[18] Wooten, E. L., et al. (2000) A review of lithium niobate modulators for fiber-optic communications systems, IEEE J. Sel. Topics Quantum Electron., 6(1): 69–82. doi: 10.1109/2944.826874.

[19] Soref, R. (2010) Silicon photonics: A review of recent literature, Silicon, 2: 1–6. doi: 10.1007/s12633-010-9034-y.

[20] Roelkens, G., Liu, L., and Van Campenhout, J. (2013) Hybrid silicon photonics: Integration and scalability, Opt. Express, 21(22): 27016–27030. doi: 10.1364/OE.21.027016.

[21] Chrostowski, L., & Hochberg, M. (2015) Silicon Photonics Design: From Devices to Systems. Cambridge, U.K.: Cambridge Univ. Press.

[22] Thomson, D., et al. (2016) Roadmap on silicon photonics, J. Opt., 18(7): 073003. doi: 10.1088/2040-8978/18/7/073003.

[23] Rahim, A., et al. (2019) Open-access silicon photonics platforms in Europe, IEEE J. Sel. Topics Quantum Electron., 25(5): 8200618. doi: 10.1109/JSTQE.2019.2915986.

[24] Shen, Y, et al. (2017) Deep learning with coherent nanophotonic circuits, Nature Photon., 11: 441–446. doi: 10.1038/nphoton.2017.93.

[25] Washburn, A. L., & Bailey, R. C. (2011) Photonics-on-a-chip: Recent advances in integrated photonic biosensors, Anal. Chem., 83(12): 4315–4321. doi: 10.1021/ac2013448.

[26] O'Brien, J. L, Furusawa, A., & Vučković, J. (2009) Photonic quantum technologies, Nature Photon., 3: 687–695. doi: 10.1038/nphoton.2009.229.

[27] Poulton, C. V., et al. (2019) Large-scale silicon nitride nanophotonic phased arrays for LIDAR, Nature Photon., 13: 528–533. doi: 10.1038/s41566-019-0421-9.

[28] Estevez, M. C., et al. (2012) Integrated optical devices for lab-on-a-chip biosensing applications, Laser Photon. Rev., 6(4): 463–487. doi: 10.1002/lpor.201100025.

DOI: 10.54254/2755-2721/2025.GL28750

[29] Shastri, B. J., et al. (2021) Photonics for artificial intelligence and neuromorphic computing, Nature Photon., 15: 102–114. doi: 10.1038/s41566-020-00754-y.