Proceedings of CONF-MLA 2025 Symposium: Intelligent Systems and Automation: AI Models, IoT, and Robotic Algorithms
DOI: 10.54254/2755-2721/2025.LD29070

Research Progress and Prospects on the Integration of Mechanical Engineering and Software in Automotive Intelligent Driving Assistance Systems

Zhixing Ding

School of Automotive Studies, Tongji University, Shanghai, China
15710187107@163.com

Abstract. This paper discusses the integration of mechanical systems and software in advanced driver-assistance systems (ADAS), focusing on functions like lane departure warning, adaptive cruise control, automatic parking, collision avoidance, driver drowsiness detection, and night-vision assistance. It examines how sensors, actuators, and advanced algorithms collaborate in each feature. Current research advances, such as multi-sensor data fusion and AI-driven perception, improve detection accuracy and response times. However, challenges persist in meeting real-time deadlines, ensuring synchronized sensor-actuator operation, and maintaining software robustness under variable conditions and cyber threats. Emerging trends like over-the-air updates, vehicle-to-everything communications, and specialized AI accelerators blur the lines between mechanical and digital domains.

Keywords: Advanced Driver-Assistance Systems, Sensor–Actuator Integration, Real-Time Control, V2X Communication, Over-the-Air Updates

1. Introduction

Advanced Driver-Assistance Systems (ADAS) are designed to improve driving safety and operational efficiency by augmenting or automating specific driving tasks [1]. Common examples include lane-keeping and departure alerts, adaptive cruise control (ACC), automatic parking, collision warning and emergency braking, driver monitoring, and night-vision support. Modern ADAS rely on diverse sensors (such as cameras, radar, LIDAR, ultrasonics), embedded software, and vehicle actuators (including steering motors, brakes, throttle control) to sense the environment and take action [2,3]. By continuously monitoring road conditions and the driver's state, ADAS can warn the driver or autonomously intervene to avoid accidents; for instance, adaptive brake control can prevent rear-end collisions in heavy traffic [4]. These systems are increasingly mandated by regulation (e.g., fatigue-detection requirements by 2024) and expected by consumers. The rapid evolution of software-defined vehicles has shifted a large part of vehicle functionality into software, with forecasts suggesting that software and electronics may comprise over half of new car value by 2030 [5]. This trend highlights the critical need for tight integration of mechanical and software components in ADAS: sensors and actuators must be precisely calibrated, control algorithms must meet strict timing deadlines, and user interfaces must convey status in real time. This paper

© 2026 The Authors. This is an open access article distributed under the terms of the Creative Commons Attribution License 4.0 (https://creativecommons.org/licenses/by/4.0/).

DOI: 10.54254/2755-2721/2025.LD29070

examines the current research on ADAS integration, focusing on core features, sensor or actuator architectures, software processing, challenges like real-time constraints, system robustness, and emerging areas like over-the-air updates, V2X connectivity, and AI hardware. This research draws on recent high-quality studies in IEEE and MDPI journals and use open-access sources wherever possible, complemented by insights from the uploaded reference materials.

2. ADAS features and mechanical–software collaboration

ADAS features rely on the seamless integration of sensor data processing, mechanical actuation and human-machine interfaces to deliver enhanced safety and convenience. Take lane departure warning (LDW) as an example. The system uses forward-facing cameras to detect road lane markings [5]. If the vehicle drifts without a turn signal, the system issues a visual, auditory, or haptic alert, and advanced lane-keeping assists can apply corrective steering via an electric motor. Adaptive cruise control (ACC) employs radar or LIDAR to measure the distance to the vehicle ahead and adjusts throttle/braking to maintain a set following distance. Here, software algorithms in the electronic control unit (ECU) interpret range data and command the engine or brake actuators to speed up or slow down smoothly [1]. In automatic parking, ultrasonic sensors and 360° cameras scan surroundings while path-planning software computes a steering and velocity profile; the steering actuator and transmission then execute the maneuver.

2.1. Core safety functions of ADAS

ADAS implements multiple safety functions through specialized sensor-software-actuator coordination. For collision avoidance and emergency braking, forward-facing radar and LiDAR detect sudden obstacles, while vision systems recognize pedestrians or cyclists; sensor fusion algorithms assess threats and trigger firm braking if needed—LiDAR's precise 3D mapping, for example, enables the ECU to initiate emergency braking before driver reaction [4]. Driver drowsiness and attention monitoring use cameras or driver-facing sensors. Computer vision tracks eye closure, gaze direction, and facial features, while steering or lane-variance metrics can also signal fatigue. When drowsiness is detected, the software alerts the driver via a visual dashboard warning, an audible alarm, or seat/steering-wheel vibration [6]. Night-vision assistance integrates infrared (IR) cameras or thermal imaging. The software processes IR images to highlight pedestrians or animals on the road; alerts are shown on a head-up or dashboard display. Mechanical integration includes orienting headlights (adaptive high-beam control) and signaling. For example, adaptive headlamps adjust the beam angle based on steering input, a mechanical action prompted by vision software that identifies curves.

2.2. The sensing-computation-actuation closed loop

All ADAS functions operate on a core closed-loop principle: sensors first acquire raw data (position, speed, images); algorithms then analyze this data (object detection, distance estimation, control law application). Finally, actuators execute commands (steering torque adjustment, braking force, haptic feedback). The loop closes when the driver or system monitors outcomes via displays or physical feedback (e.g., steering response), ensuring effective operation.

DOI: 10.54254/2755-2721/2025.LD29070




Figure 1. Typical ADAS sensor layout and coverage zones in a vehicle (front radar for ACC/AEB, side ultrasonic for parking, rear camera for backup, etc.)

As shown in Figure 1, Advanced ADAS uses multiple sensors to provide overlapping fields of view, including front radars, LIDAR, cameras, and side/rear sensors. Software on embedded processors combines these inputs to build a driving environment model and compute appropriate control actions, forming mechatronic systems with mechanical and electronic components.

3. Integration of sensing, decision, and actuation

Modern vehicles employ rich sensor suites to feed ADAS software. Radar sensors, operating at millimeter-wave frequencies, measure object range and speed reliably in rain or fog. They are key to ACC and collision mitigation. LIDAR provides high-resolution 3D mapping; despite sensitivity to weather, it excels at parking and obstacle detection. Vision cameras capture color and texture, ideal for lane markings, traffic signs, and pedestrian recognition, but require good lighting. Vehicles often also have ultrasonic sensors for short-range parking assist. Each sensor type requires software preprocessing (e.g., point-cloud processing, image filtering). Sensor fusion algorithms then correlate data (e.g., matching radar detections to camera images) to improve reliability [1,3]. Once the environment is understood, decision-making software evaluates risks. Machine learning (ML) and deep neural networks are increasingly used for perception tasks. For example, recent work shows DCNN models classifying pedestrians in RGB/IR camera feeds with >97% accuracy [7]. ADAS ECU algorithms run on specialized hardware, detect vehicle detection, compute actuation, and implement commands through steering-by-wire motors, brake-by-wire actuators, and throttle actuators. These mechanical systems, commanded by electronic signals, provide driver feedback and lane-keeping assistance. Displays and sounds complete the human–machine interface. Together, these hardware elements and the real-time software create a closed-loop control system (Fig.2), requiring tight synchronization.

DOI: 10.54254/2755-2721/2025.LD29070




Figure 2. End-to-end ADAS closed loop with critical timing and synchronization requirements

Research on autonomous driving systems (ADAS) is advancing, with advancements in multi-sensor fusion and AI-driven models. A recent system combines an IR camera, a visible camera, and a micro-Doppler radar to detect pedestrians, providing a vibration alert and on-screen warning instantly. This demonstrates how integrating diverse sensors with machine learning can improve detection robustness under various conditions [8]. However, gaps and challenges remain, such as sensor calibration and synchronization with vehicle dynamics, and drivers' complaints about false alarms or intrusive behavior. This suggests the need for active research in software tuning and interface design.

4. Integration challenges and open issues

Integrating mechanical and software systems in ADAS introduces several technical challenges:

ADAS faces numerous challenges in real-time performance, system coordination, software safety, security, and environmental adaptation. Real-time constraints require quick decisions, such as emergency braking, and require software to process sensor data, run algorithms, and send commands without delay. Onboard systems must be optimized for determinism, and sensor-actuator coordination requires precise time synchronization for smooth decision-making. End-to-end data flow management is complex, and mismatches can cause incorrect actuation. Software robustness and safety require fault tolerance to handle sensor noise, occlusions, and cyber-physical attacks. Integrating ML modules alongside real-time control creates verification challenges, making reliability under all conditions a major open problem. Security and OTA update challenges require maintaining calibration and functionality accuracy during over-the-air updates in Figure 3, as software changes may require camera re-calibration. Environmental variability affects mechanical sensors via weather and lighting, requiring software compensation and mechanical design considerations to ensure robustness. In summary, while individual ADAS technologies have advanced, their system-level integration still confronts issues of real-time data flow, system safety, and coordinated updates. These problems cut across traditional domains: they are simultaneously mechanical (physical actuator limits), electrical (sensor design), and software (algorithmic and security) challenges.

DOI: 10.54254/2755-2721/2025.LD29070




Figure 3. End-to-end OTA update process with security safeguards and calibration consistency requirements

5. Emerging technologies in ADAS integration

Beyond core ADAS functions, several emerging technologies highlight the mechanical-software nexus: Modern ADAS is shaped by three transformative technological trends: Over-the-Air (OTA) updates allow vehicles to receive firmware/software updates for ECUs, enabling continuous ADAS algorithm improvement without hardware changes—Tesla, for instance, has notably enhanced braking performance via such updates—but OTA also requires aligning software and mechanical calibration, as altering sensor thresholds or control logic via updates may demand actuator recalibration, so OTA frameworks must manage both software bits and the vehicle's physical alignment [9,10]. Additionally, Vehicle-to-Everything (V2X) communication adds external data to ADAS, adding a network sensor. Integrating V2X requires software to fuse remote data with onboard sensor inputs, with research using it as a redundant safety layer and future work integrating it into core environmental modeling [11]. Furthermore, ADAS's AI-driven adoption surpasses traditional microcontrollers, leading to the use of custom chips like NVIDIA Drive, Qualcomm Snapdragon Ride, and Mobileye EyeQ, blurring hardware/software boundaries. Edge AI trends also suggest future ADAS functions may shift between in-vehicle local computing and cloud-based services, necessitating robust software abstraction follow Figure 4. The line between mechanical and software is blurring, with features like brakes and ECUs becoming software-controlled subsystems. Integration requires co-design between engineers and developers.

DOI: 10.54254/2755-2721/2025.LD29070




Figure 4. Synergy between AI inference hardware and vehicle mechanical/electrical design constraints

6. Conclusion

Looking ahead, Advanced Driver Assistance Systems (ADAS) will keep advancing toward higher levels of autonomy, with two key trends coming to the fore: tighter mechatronic integration and wider industry standardization. A typical example of this shift is the gradual replacement of discrete Electronic Control Units (ECUs) by domain controllers—centralized computing platforms designed to handle multiple vehicle functions. This could simplify synchronization but raise the bar for software reliability. Connectivity (5G/6G) will enable cooperative ADAS: vehicles may share sensor data peer-to-peer for collective perception, requiring extremely low-latency networking and security. AI will play an even larger role: deep learning models will power end-to-end perception and decision-making, demanding more powerful automotive processors and redundant safety architectures. Simultaneously, machine learning will help calibrate and adapt ADAS systems over time. True software/hardware co-design is needed so that future vehicles can learn and improve continuously, effectively becoming smarter mechanical systems.

References

[1] Wang, Z., Wu, Y., & Niu, Q. (2019). Multi-sensor fusion in automated driving: A survey. IEEE Access, PP(99), 1–1. https: //doi.org/10.1109/ACCESS.2019.2962554

[2] Abdelkader, G. (2021). Connected vehicles: Technology review, state of the art, and vision for future applications. Sensors, 21(22), 7712. https: //doi.org/10.3390/s21227712

[3] Nagvekar, A. (2025). The rise of artificial intelligence in ADAS and autonomous vehicles: Progress and challenges. International Journal of Research in Computer Applications and Information Technology, 8(1), 3094–3108.

[4] Hamidaoui, M., Talhaoui, M. Z., Li, M., Midoun, M. A., Haouassi, S., Mekkaoui, D. E., Smaili, A., Cherraf, A., & Benyoub, F. Z. (2025). Survey of autonomous vehicles' collision avoidance algorithms. Sensors, 25(2), 395. https: //doi.org/10.3390/s25020395

DOI: 10.54254/2755-2721/2025.LD29070

[5] Waykole, S., Shiwakoti, N., & Stasinopoulos, P. (2021). Review on lane detection and tracking algorithms of advanced driver assistance systems. Sustainability, 13(20), 11417. https: //doi.org/10.3390/su132011417
[6] Albadawi, Y., Takruri, M., & Awad, M. (2022). A review of recent developments in driver drowsiness detection systems. Sensors, 22(5), 2069. https: //doi.org/10.3390/s22052069
[7] Nagvekar, A. (2025). The rise of artificial intelligence in ADAS and autonomous vehicles: Progress and challenges. International Journal of Research in Computer Applications and Information Technology, 8(1), 3094–3108.
[8] Kulhandjian, H., Barron, J., Tamiyasu, M., Thompson, M., & Kulhandjian, M. (2024). AI-based pedestrian detection and avoidance at night using multiple sensors. Journal of Sensor and Actuator Networks, 13(3), 34. https: //doi.org/10.3390/jsan13030034
[9] Luo, Y., & Lu, S. (2025). Incremental Over-the-Air Update for Software-Defined Vehicles with C-V2X. In Proceedings of the 101st IEEE Vehicular Technology Conference (VTC2025-Spring).
[10] Li, B., Hu, W., Da, L., Wu, Y., Wang, X., Li, Y., & Yuan, C. (2024). Over-the-air upgrading for enhancing security of intelligent connected vehicles: A survey. Artificial Intelligence Review, 57(11), 314.
[11] Yusuf, S. A., et al. (2024). Vehicle-to-everything (V2X) in the autonomous domain: A review. Vehicular Communications. https: //doi.org/10.1016/j.vehcom.2023.100227