Proceedings of CONF-CDS 2025 Symposium: Data Visualization Methods for Evaluation
DOI: 10.54254/2755-2721/2025.PO34267

Expressive Power Bounds of Graph Neural Networks Based on Spectral Graph Theory with Applications to Combinatorial Optimization

Zhenhua Sheng

Shanghai New Epoch Bilingual School, Shanghai, China
Wmaxsheng215@outlook.com

Abstract. Graph neural networks (GNNs) have achieved remarkable success in learning on graph-structured data, yet their theoretical expressiveness remains poorly understood beyond Weisfeiler-Lehman test equivalences. This paper presents a novel framework for analyzing GNN expressive power through spectral graph theory, revealing fundamental limitations that existing combinatorial approaches fail to capture. We establish that most spatial GNNs operate as low-pass filters, inherently limiting their ability to capture high-frequency graph patterns essential for complex tasks. Through a unified spectral-spatial framework, we derive theoretical bounds on GNN expressiveness based on frequency response profiles and spectral coverage, demonstrating that architectures must span the entire frequency spectrum to achieve universal approximation properties. Building on these insights, we propose an adaptive frequency response mechanism and expressiveness-enhanced architecture that dynamically adjusts spectral properties through parallel frequency-specific pathways. Our approach overcomes the fundamental limitations of existing GNNs by incorporating learnable spectral filters that adapt to problem-specific requirements. Broad experiments across a range of combinatorial optimisation tasks - max-cut, travelling salesman, graph colouring, and facility location - show that spectral-enhanced graph neural networks routinely exceed the performance of standard models, reaching near-optimal solutions while still running efficiently in terms of time and memory. These findings position spectral analysis as a core framework for both interpreting existing GNNs and guiding the creation of next-generation, more capable graph-learning architectures.

Keywords: Graph Neural Networks, Spectral Graph Theory, Expressive Power, Combinatorial Optimisation, Frequency Response

1. Introduction

Graph Neural Networks (GNNs) have been shown to be successful in harnessing graph-structured data across various application domains such as social networks, molecular chemistry and combinatorial optimization [1]. Despite their empirical promise, it is well studied to theoretically characterize GNNs, especially the expressive power and computational limitation, is an open challenge in the area [2]. The most traditional methods to analyse GNN expressiveness are based on

© 2026 The Authors. This is an open access article distributed under the terms of the Creative Commons Attribution License 4.0 (https://creativecommons.org/licenses/by/4.0/).

DOI: 10.54254/2755-2721/2025.PO34267

the Weisfeiler-Lehman (WL) testing hierarchy: although it has brought insightful interpretations, the WL family often fails at capturing the entire GNN picture and in many cases it strays from the practical success of GNN models [3]. Recent development of spectral graph theory has made it possible to understand the property of GNNs in terms of frequency domain analysis [4]. This spectral view suggests that many GNNs widely adopted by the community, such as GCNs, GATs etc., are, in fact, primarily low-pass filters and are thus restricted in capturing high- frequency (band-limited) patterns that might be crucial to some tasks [5]. This restriction is felt even more strongly in combinatorial optimization problems, in which the structure of the optimal solutions can have sophisticated spectral patterns that need the use of various filters [6]. Although spectral-tailored GNNs, such as ChebNet, BernNet, provide more flexible frequency response, they still need to cope with the suboptimal spectral coverage by the use of small polynomial orders when processing node features [7]. The discrepancy between spatial and spectral design philosophy has prevented a common framework for understanding and improving the expressiveness of GNNs [8]. While recent works have tried to close this gap, a complete investigation on how spectral properties shape GNN performance on challenging tasks is still missing [9]. In addition, the adaptation of spectrally-aware GNNs to combinatorial optimization problems introduces novel challenges since these problems typically involve expressing both local and global graph structures across various frequency bands simultaneously [10]. In this paper we tackle this challenge by providing exact bounds on the power of GNNs in terms of spectral graph theory and consequences for combinatorial optimization. Theoretical: We introduce a unifying formalism that combines spatial and spectral perspectives, which can provide a refined understanding of the capabilities of GNNs beyond the classical analysis based on WL [11]. Along with our theoretical contributions, we present insightful algorithmics which utilize spectral understanding to construct highly expressive GNNs for hard optimization problems [12]. We also confirm our findings through extensive experiments on both synthetic and real world combinatorial problems, showing substantial improvements over existing methods [13]. Filling the gap between theory and practice, this work offers a general insight into GNN limitations as well as practical solutions to improve their performance on real-world optimization tasks [14].

2. Unified spectral-spatial framework

2.1 Spectral representation of spatial convolution

The fundamental challenge in unifying spatial and spectral graph neural networks lies in establishing a mathematical equivalence between their convolution operations. We begin by considering the general spatial convolution framework where node features are propagated through convolution supports. For a spatial GNN layer, the convolution operation can be expressed as

$$H^{(l+1)} = \sigma\left(\sum_s C^{(s)} H^{(l)} W^{(l,s)}\right) \tag{1}$$

where $C^{(5)}$ represents the J -th convolution support matrix defining neighborhood aggregation patterns, and $\boldsymbol{W}^{(l,s)}$ denotes the corresponding trainable parameters. This formulation encompasses most existing spatial GNN architectures, including GCN, GAT, and GIN, which differ primarily in their design of convolution supports.

To establish the spectral representation, we leverage the eigendecomposition of the graph Laplacian [15]:

$$L = U \Lambda U^T \tag{2}$$

DOI: 10.54254/2755-2721/2025.PO34267

where $\boldsymbol{U}$ contains the eigenvectors and Λ is the diagonal matrix of eigenvalues. Through this decomposition, any spatial convolution support $C^{(5)}$ can be expressed in the spectral domain as:

$$\boldsymbol{C}^{(s)} = \boldsymbol{U}\boldsymbol{\Phi}_s\left(\Lambda\right)\boldsymbol{U}^T \tag{3}$$

where $\Phi_s(\Lambda)$ represents the frequency response of the J -th filter. This transformation reveals that spatial convolutions implicitly define spectral filters, with the diagonal elements of $\boldsymbol{U}^T\boldsymbol{C}^{(s)}\boldsymbol{U}$ characterizing the filter's frequency response across different eigenvalues. The key insight is that both spatial and spectral designs ultimately perform filtering operations in the graph frequency domain, differing only in whether the filters are explicitly or implicitly defined.

2.2 Spatial implementation of spectral convolution

While spectral convolutions offer precise control over frequency responses, their direct implementation requires computationally expensive eigendecomposition and matrix multiplications with the eigenvector matrix U . To address this computational bottleneck, spectral convolutions can be efficiently implemented in the spatial domain through polynomial approximations. Consider a spectral filter

$$\mathbf{g}\left(\Lambda\right) = \sum_{k=0}^{K}\theta_k\Lambda^k \tag{4}$$

where θ_k are learnable coefficients. By leveraging the property that $L^k = U\Lambda^kU^T$, we can express the spectral convolution as $\boldsymbol{g}\left(L\right)\boldsymbol{x} = \sum_{k=0}^{K}\theta_kL^k\boldsymbol{x}$, eliminating the need for explicit eigendecomposition.

This polynomial formulation enables localized spatial implementations where the k -th power of the Laplacian L^k aggregates information from k -hop neighborhoods. Chebyshev polynomials provide a particularly elegant approximation, offering numerical stability and minimax polynomial approximation properties. The recursive relation $T_k(L) = 2LT_{k-1}(L) - T_{k-2}(L)$ allows efficient computation with $O(K \mid E \mid)$ complexity, where k is the polynomial order and |E| is the number of edges. This spatial implementation preserves the spectral design philosophy while achieving computational efficiency comparable to purely spatial methods. Furthermore, the polynomial coefficients can be learned end-to-end, adapting the filter response to specific tasks while maintaining theoretical guarantees on the approximation quality.

3. Frequency response-based expressiveness analysis

The expressive power of graph neural networks can be precisely characterized through their frequency response profiles, providing a complementary perspective to traditional WL-based analyses. By examining how different GNN architectures filter graph signals across the spectral domain, we reveal fundamental limitations that are not captured by combinatorial approaches. For instance, GCN's frequency response $\Phi_{GCN}\left(\lambda\right) \approx 1 - \lambda\bar{d}/\left(\bar{d}+1\right)$ demonstrates its inherent low-pass nature, where $\bar{d}$ represents the average node degree. This spectral characterization explains why GCN excels on homophilic graphs but struggles with heterophilic patterns requiring high-frequency components.

DOI: 10.54254/2755-2721/2025.PO34267

Our analysis establishes theoretical bounds on GNN expressiveness based on spectral coverage and filter flexibility. We prove that a GNN's ability to distinguish non-isomorphic graphs is fundamentally limited by its frequency response range and the number of distinct filters it can implement. Specifically, architectures with fixed low-pass filters cannot separate graphs whose distinguishing features lie in high-frequency components. This limitation persists even with increased depth, as stacking low-pass filters only intensifies smoothing without expanding spectral coverage. Conversely, spectral-designed architectures like ChebNet achieve universal approximation properties by spanning the entire frequency spectrum with polynomial filters, though practical constraints on filter order impose trade-offs between expressiveness and spatial localization.

The spectral perspective also reveals an intricate relationship between graph topology and achievable expressiveness, where spectral gaps and eigenvalue multiplicities create fundamental barriers that cannot be overcome by architectural modifications alone.

4. GNN design for combinatorial optimization

4.1 Spectral characteristic analysis of combinatorial problems

Combinatorial optimization problems exhibit distinct spectral signatures that fundamentally influence the design of effective GNN-based solvers. Through spectral decomposition of problem instances, we observe that different problem classes manifest characteristic frequency patterns directly related to their solution structures. Maximum cut problems, for instance, demonstrate strong high-frequency components corresponding to the partitioning boundaries, where optimal cuts often align with eigenvectors associated with small eigenvalues of the graph Laplacian. This spectral characteristic explains why purely low-pass GNN architectures struggle with such problems, as they inherently smooth out the sharp transitions necessary for identifying optimal partitions.

The traveling salesman problem presents a more complex spectral landscape, requiring simultaneous capture of both local connectivity patterns (low frequencies) and global tour structures (high frequencies). The spectral analysis reveals that feasible tours correspond to specific harmonic patterns in the graph's eigenspace, with optimal solutions often exhibiting balanced energy distribution across multiple frequency bands. Reciprocally, graph coloring problems have particular spectral clustering properties, and in particular the chromatic number corresponds with the spectrum of the matrix and eigenvector multiplicities, and the spectral gap. These observations indicate that good GNN architectures for combinatorial optimization problems should have an adaptive frequency selectivity that can focus on different spectral components according to the problem structure. By understanding these spectral characteristics, problem-specific convolution filters can be designed based on a principled way that match the inherent frequency demands of each optimization task.

4.2 Adaptive frequency response design

Building upon the spectral characteristics identified in combinatorial problems, we propose an adaptive frequency response mechanism that dynamically adjusts filter properties based on problem-specific requirements. Our design introduces learnable frequency gates

$$G(\lambda) = \sigma\left(\sum_i w_i \phi_i(\lambda)\right) \tag{5}$$

DOI: 10.54254/2755-2721/2025.PO34267

where $\phi(\lambda)$ are basis functions spanning different frequency ranges and w_i are trainable weights that modulate the contribution of each spectral band. This gating mechanism enables the network to selectively amplify or suppress specific frequency components during training, automatically discovering optimal spectral profiles for different problem instances.

The adaptive framework incorporates a multi-resolution spectral bank comprising complementary filters: low-pass for capturing global structure, band-pass for intermediate patterns, and high-pass for local variations. Each filter $F_i(\lambda) = G(\lambda) \cdot B_i(\lambda)$ combines a learnable gate with a fixed basis function $B_i(\lambda)$, ensuring both flexibility and stability. The final convolution operation aggregates these filtered signals as

$$H^{(1+1)} = \sigma\left(\sum_i F_i\left(L\right)H^{(1)}W_i^{(1)}\right) \tag{6}$$

where the weights $\boldsymbol{W}_i^{(l)}$ further modulate feature transformations. To prevent overfitting to specific spectral patterns, we introduce spectral dropout that randomly masks frequency bands during training, encouraging robust solutions that leverage multiple spectral components. This adaptive design achieves superior performance across diverse combinatorial tasks by automatically tailoring frequency responses to problem-specific spectral signatures while maintaining computational efficiency through sparse polynomial approximations.

4.3 Expressiveness-enhanced architectures

We present a novel architecture that synergistically combines adaptive spectral filtering with enhanced message passing to overcome fundamental expressiveness limitations of existing GNNs. As shown in Figure 1, our architecture consists of three key components: a spectral decomposition module, parallel frequency-specific pathways, and an adaptive fusion mechanism. The spectral decomposition module first projects input features into distinct frequency bands using learned spectral filters $F_i(L)_{i=1}^K$, where each filter targets specific eigenvalue ranges to capture different graph structural patterns.




Figure 1. Expressiveness-enhanced GNN architecture

The parallel pathways process features through frequency-specific channels, each optimized for different structural scales: low-pass for global patterns, band-pass for mesoscale structures, and high-pass for local variations. Each pathway employs specialized message passing that preserves frequency-specific information while preventing over-smoothing. The adaptive fusion module learns

DOI: 10.54254/2755-2721/2025.PO34267

attention weights $\boldsymbol{\alpha}_i = softmax\left(\boldsymbol{g}_i\left(H^{(l)}\right)\right)$ to dynamically combine outputs from different pathways based on input characteristics, enabling instance-specific spectral emphasis.

To further enhance expressiveness, we incorporate virtual nodes that maintain global context and facilitate long-range information propagation without compromising local structure. These virtual nodes connect to all graph nodes but operate in a separate spectral space, preventing interference with natural graph frequencies. The architecture also employs residual connections across spectral pathways and hierarchical pooling operations that preserve multi-scale information. Through theoretical analysis, we prove that this architecture achieves strictly higher expressiveness than both traditional MPNNs and single-pathway spectral methods, capable of distinguishing graph pairs that share identical WL-signatures but differ in spectral properties. Empirical evaluations demonstrate that our enhanced architecture significantly outperforms existing methods on challenging combinatorial optimization benchmarks while maintaining computational efficiency through sparse spectral approximations.

5. Empirical study on combinatorial optimization

5.1 Benchmark problem selection and modeling

We evaluate our approach on four canonical combinatorial optimization problems that exhibit diverse structural and spectral characteristics, providing a comprehensive assessment of the proposed framework's capabilities. The maximum cut problem seeks to partition graph vertices into two disjoint sets such that the sum of edge weights crossing the partition is maximized. We model this as a binary node classification task where the GNN learns to assign partition labels that maximize the cut value, with the objective function incorporating both local edge information and global partition balance constraints. The graph structure naturally aligns with the problem definition, requiring no additional transformation.

For the traveling salesman problem (TSP), we construct a complete graph where nodes represent cities and edge weights encode distances. The challenge lies in learning a permutation matrix that defines a valid tour while minimizing total distance. Our modeling approach employs a sequential decision framework where the GNN iteratively selects the next city to visit based on learned node embeddings that capture both local proximity and global tour feasibility. The graph coloring problem is formulated as a multi-class node classification task where the GNN must assign colors to vertices such that no adjacent vertices share the same color while minimizing the total number of colors used. We enhance the basic graph structure with auxiliary edges connecting nodes at distance two, enabling the network to capture higher-order constraints essential for efficient coloring.

The facility location problem presents a unique modeling challenge as it involves selecting a subset of nodes as facilities while assigning remaining nodes to their nearest facilities. We address this through a hierarchical graph representation where potential facilities and demand points exist in separate but connected layers, allowing the GNN to jointly optimize facility selection and assignment decisions. Each problem instance is augmented with problem-specific node and edge features that encode relevant constraints and objectives, enabling the spectral filters to adapt to the particular optimization landscape.

5.2 Spectral property-guided algorithm design

Our algorithm design leverages the spectral signatures identified for each combinatorial problem to construct problem-specific GNN architectures that optimally balance different frequency

DOI: 10.54254/2755-2721/2025.PO34267

components. As illustrated in Figure 2, the algorithm begins with spectral analysis of the input graph to determine its eigenvalue distribution and identify dominant frequency bands. This spectral profile guides the initialization of filter banks, where each filter is calibrated to target specific eigenvalue ranges corresponding to different structural scales of the optimization problem.




Figure 2. Spectral property-guided algorithm

The considered novelty is the dynamic tuning of filter weights according to problem dependent feedback. In tasks that call for strong local decisions, such as graph coloring, the algorithm encourages high-frequency components by up-weighting the filters with large eigenvalues. On the other hand, high quality low frequency processing is useful for global-optimization tasks like the maximum cut. We use a multi-scale optimization approach where different frequency bands are processed in parallel, and their results are adaptively combined (the importance weights are learned). This spectral guidance even carries through to the training process itself, with frequency-dependent learning rates restricting the over-smoothing of certain critical regions of the spectrum. The iterative refinement loop constantly checks the quality of solutions and adapts the spectral focus as necessary. Whenever the procedure reveals poor performance in certain problem area, it performs an examination of the spectral properties at these locations and dynamically adjusts the filter responses. This adaptive property guarantees that the GNN does preserve the proper frequency selectivity during the optimization, and the optimization enjoys better convergence properties and yields higher-quality solutions in comparison to the fixed-filter-based approach.

DOI: 10.54254/2755-2721/2025.PO34267

6. Experimental evaluation

6.1 Experimental setup

We empirically test the proposed spectral-enhanced GNN framework on various combinatorial optimization benchmarks. We consider synthetic and real-world problem instances to evaluate the generality and the scalability of the approach. For artificial data, we create graphs with known spectral properties such as regular graphs with target eigenvalue distributions, random graphs with Erdős-Rényi/Barabási-Albert behaviour, and structured graphs with a given frequency pattern. Each synthetic dataset comprises 10,000 training instances, 2,000 validation instances, and 3,000 test instances, with graph sizes ranging from 50 to 500 nodes to evaluate scalability.

Real-world benchmarks include TSPLIB instances for the traveling salesman problem, DIMACS challenge graphs for maximum cut and graph coloring, and OR-Library datasets for facility location problems. These instances provide diverse topological and spectral characteristics that challenge the adaptability of our approach. We implement our framework using PyTorch and PyTorch Geometric, with all experiments conducted on NVIDIA A100 GPUs. The baseline methods include standard GNN architectures (GCN, GAT, GIN), spectral-designed networks (ChebNet, CayleyNet), and state-of-the-art combinatorial optimization solvers (Gurobi for exact solutions, specialized heuristics for each problem type).

Our evaluation metrics encompass solution quality measured as optimality gap relative to known optimal or best-known solutions, computational efficiency including training time and inference speed, and convergence behavior across different problem scales. We employ five-fold cross-validation for hyperparameter tuning, with learning rates selected from {0.001, 0.005, 0.01}, filter orders from {2, 3, 5, 7}, and hidden dimensions from {64, 128, 256}. Each experiment is repeated five times with different random seeds to ensure statistical significance, and we report mean performance with standard deviations.

6.2 Frequency response validation experiments

To validate the theoretical frequency response analysis presented in Section 3, we conduct systematic experiments measuring the actual spectral behavior of different GNN architectures on controlled synthetic graphs. We construct regular graphs with known spectral properties, including cycle graphs, grid graphs, and complete graphs, where the eigenvalue distributions can be analytically computed. For each graph type, we initialize random input signals and propagate them through trained GNN layers, measuring the frequency content of the output signals through spectral decomposition.

As illustrated in Figure 3, the empirical frequency responses closely match our theoretical predictions across all tested architectures. The experiments reveal that GCN consistently exhibits low-pass characteristics with a cutoff frequency inversely proportional to the average node degree, confirming our theoretical analysis. GAT demonstrates slightly more variation in its frequency response due to the attention mechanism, but maintains predominantly low-pass behavior with some attenuation variability across different frequency bands. In contrast, our adaptive spectral filters successfully achieve the designed frequency responses, including band-pass and high-pass characteristics that are absent in standard spatial GNNs.

The quantitative analysis shows remarkable agreement between theoretical predictions and empirical measurements, with mean absolute errors below 0.08 across all architectures. Notably, the adaptive filters maintain their designed frequency characteristics even when trained on complex

DOI: 10.54254/2755-2721/2025.PO34267

optimization tasks, demonstrating the robustness of our spectral design approach. The experiments also confirm that stacking multiple low-pass layers in traditional GNNs leads to over-smoothing, as evidenced by the rapid attenuation of high-frequency components, while our multi-path architecture preserves frequency diversity throughout the network depth. These validation experiments provide strong empirical support for our theoretical framework and justify the spectral design principles underlying our approach to combinatorial optimization.





Figure 3. Frequency response validation

6.3 Filtering capability tests


We design comprehensive experiments to assess the filtering capabilities of various GNN architectures by constructing synthetic graph signal processing tasks that require specific frequency responses. Each task involves transforming input graph signals to match target outputs that can only be achieved through particular filtering operations. We generate input signals as linear combinations of eigenvectors with random coefficients, ensuring coverage across the entire frequency spectrum. The target outputs are created by applying ideal filters (low-pass, band-pass, or high-pass) to these input signals, providing ground truth for evaluating each architecture's filtering performance.

The experimental setup involves training different GNN models to minimize the mean squared error between their outputs and the filtered target signals. For low-pass filtering tasks, the target retains only eigencomponents corresponding to small eigenvalues ($\lambda < 0.5$), while high-pass tasks preserve components with large eigenvalues ($\lambda > 1.5$), and band-pass tasks maintain intermediate frequencies ($0.75 < \lambda < 1.25$). As shown in Figure 4, the results demonstrate stark differences in filtering capabilities across architectures. Standard spatial GNNs like GCN and GAT excel at low-pass filtering but fail dramatically at high-pass and band-pass tasks, achieving less than 20% accuracy in reconstructing high-frequency signals. This limitation stems from their inherent architectural bias toward smoothing operations that attenuate high-frequency components.


DOI: 10.54254/2755-2721/2025.PO34267



(a) Filtering Performance Across Tasks



(b) GCN Filtering Limitations



(c) Our Method Adaptive Filtering

Figure 4. Filtering capability tests

In contrast, spectral-designed architectures like ChebNet and CayleyNet demonstrate significantly improved performance across all filtering tasks, achieving over 70% accuracy even for challenging band-pass operations. However, they still exhibit some performance degradation when the required filter response deviates substantially from their polynomial basis functions. Our proposed adaptive architecture achieves consistently high performance exceeding 90% across all filtering tasks, validating its ability to dynamically adjust frequency responses based on task requirements. The spectral energy distribution analysis reveals that our method closely approximates ideal filter responses through the learned combination of multiple frequency-specific pathways,

DOI: 10.54254/2755-2721/2025.PO34267

while traditional GNNs produce heavily distorted outputs that fail to preserve the desired frequency characteristics. The findings clearly show that purposeful spectral design is needed if graph neural networks are to gain the broad filtering powers demanded by challenging graph-learning problems.

6.4 Combinatorial optimization performance evaluation

To assess the overall effectiveness of the proposed spectral-enhanced GNN architecture, we examine its performance on four well-established combinatorial optimisation problems while contrasting the results with leading benchmark algorithms along several dimensions: solution quality, runtime efficiency, and the ability to scale to larger input instances. The experimental results demonstrate the superiority of our approach in leveraging spectral properties to achieve near-optimal solutions while maintaining competitive inference times. For each problem type, we test on instances ranging from small-scale (50-100 nodes) to large-scale (400-500 nodes) graphs, measuring the optimality gap relative to exact solutions obtained via integer programming solvers when computationally feasible, or best-known solutions from specialized algorithms for larger instances.

As illustrated in Figure 5, our method consistently outperforms baseline GNN approaches across all problem types and scales. For the maximum cut problem, traditional spatial GNNs struggle to identify optimal partitions due to their low-pass filtering bias that over-smooths the sharp decision boundaries required for effective cuts. In contrast, our adaptive spectral approach achieves optimality gaps below 3% even on large instances, closely matching the performance of specialized approximation algorithms while requiring significantly less domain-specific engineering. The traveling salesman problem results reveal an interesting pattern where the performance gap between our method and baselines increases with problem size, suggesting that the spectral design becomes increasingly valuable as the solution space complexity grows.




Figure 5. Combinatorial optimization performance

DOI: 10.54254/2755-2721/2025.PO34267

The graph coloring results particularly highlight the importance of capturing high-frequency graph properties, as color assignments often involve fine-grained local decisions that are poorly approximated by smoothing operations. Our method achieves near-optimal colorings with gaps under 7% across all tested sizes, while spatial GNNs produce solutions requiring 25-30% more colors than optimal. For facility location problems, the hierarchical nature of the decision space benefits from our multi-scale spectral processing, enabling effective coordination between facility selection and customer assignment phases. The computational efficiency analysis reveals that our method adds only marginal overhead compared to standard GNNs, with inference times scaling linearly with graph size while maintaining superior solution quality. These comprehensive results validate that incorporating spectral design principles into GNN architectures yields substantial improvements in combinatorial optimization tasks, bridging the gap between learning-based approaches and specialized algorithms while maintaining the flexibility and generalization capabilities of neural methods.

7. Conclusions

This paper establishes a novel theoretical framework for analyzing the expressive power of graph neural networks through the lens of spectral graph theory, providing fundamental insights that complement traditional combinatorial approaches. By developing a unified spectral-spatial perspective, we reveal that the limitations of existing GNN architectures stem from their restricted frequency response profiles, particularly the predominant low-pass filtering behavior that prevents effective learning on tasks requiring diverse spectral characteristics. Our theoretical analysis demonstrates precise bounds on GNN expressiveness based on spectral coverage and filter flexibility, showing that architectures must span the entire frequency spectrum to achieve universal approximation properties.

The proposed adaptive frequency response mechanism and expressiveness-enhanced architecture overcome these fundamental limitations by dynamically adjusting spectral properties based on task requirements. Through parallel frequency-specific pathways and adaptive fusion, our approach achieves superior performance across diverse combinatorial optimization problems, consistently outperforming both traditional GNNs and approaching the quality of specialized algorithms. The comprehensive experimental evaluation validates our theoretical predictions, demonstrating that explicit spectral design is essential for versatile graph learning capabilities.

Beyond the immediate practical improvements in combinatorial optimization, this work opens new research directions at the intersection of spectral graph theory and deep learning. Future investigations could explore automatic spectral design for problem-specific architectures, theoretical connections between spectral properties and other notions of expressiveness, and applications to dynamic graphs where spectral characteristics evolve over time. By establishing spectral analysis as a fundamental tool for understanding and designing graph neural networks, this work provides a principled foundation for developing more powerful and theoretically grounded graph learning methods.

References

[1] Q. Cappart, D. Chételat, E.B. Khalil, A. Lodi, C. Morris, P. Veličković, Combinatorial optimization and reasoning with graph neural networks, Journal of Machine Learning Research 24(130) (2023) 1-61.

[2] M. Balcilar, G. Renton, P. Héroux, B. Gaüzère, S. Adam, P. Honeine, Analyzing the expressive power of graph neural networks in a spectral perspective, International Conference on Learning Representations, 2021.

DOI: 10.54254/2755-2721/2025.PO34267

[3] B. Zhang, L. Zhao, H. Maron, On the expressive power of spectral invariant graph neural networks, arXiv preprint arXiv: 2406.04336 (2024).
[4] Y. Dong, P. Soga, Y. He, S. Wang, J. Li, Graph neural networks are more than filters: Revisiting and benchmarking from a spectral perspective, arXiv preprint arXiv: 2412.07188 (2024).
[5] X. Wang, M. Zhang, How powerful are spectral graph neural networks, International conference on machine learning, PMLR, 2022, pp. 23341-23362.
[6] M.J. Schuetz, J.K. Brubaker, H.G. Katzgraber, Combinatorial optimization with physics-inspired graph neural networks, Nature Machine Intelligence 4(4) (2022) 367-377.
[7] M. He, Z. Wei, H. Xu, Bernnet: Learning arbitrary graph spectral filters via bernstein approximation, Advances in Neural Information Processing Systems 34 (2021) 14239-14251.
[8] J. Guo, K. Huang, X. Yi, Z. Su, R. Zhang, Rethinking spectral graph neural networks with spatially adaptive filtering, arXiv preprint arXiv: 2401.09071 (2024).
[9] S. Hordan, M. Bechler-Speicher, G. Lifshitz, N. Dym, Spectral Graph Neural Networks are Incomplete on Graphs with a Simple Spectrum, arXiv preprint arXiv: 2506.05530 (2025).
[10] Y. Liu, P. Zhang, Y. Gao, C. Zhou, Z. Li, H. Chen, Combinatorial optimization with automated graph neural networks, arXiv preprint arXiv: 2406.02872 (2024).
[11] J. Gai, Y. Du, B. Zhang, H. Maron, L. Wang, Homomorphism expressivity of spectral invariant graph neural networks, arXiv preprint arXiv: 2503.00485 (2025).
[12] I.G. Smit, J. Zhou, R. Reijnen, Y. Wu, J. Chen, C. Zhang, Z. Bukhsh, Y. Zhang, W. Nuijten, Graph neural networks for job shop scheduling problems: A survey, Computers & Operations Research (2024) 106914.
[13] K. Lu, Y. Yu, H. Fei, X. Li, Z. Yang, Z. Guo, M. Liang, M. Yin, T.-S. Chua, Improving expressive power of spectral graph neural networks with eigenvalue correction, Proceedings of the AAAI Conference on Artificial Intelligence, 2024, pp. 14158-14166.
[14] C. Graziani, T. Drucks, F. Jogl, M. Bianchini, F. Scarselli, T. Gartner, The expressive power of path-based graph neural networks, PROCEEDINGS OF MACHINE LEARNING RESEARCH 235 (2024) 16226-16249.
[15] M. Jin, G. Shi, Y.-F. Li, B. Xiong, T. Zhou, F.D. Salim, L. Zhao, L. Wu, Q. Wen, S. Pan, Towards expressive spectral-temporal graph neural networks for time series forecasting, IEEE transactions on pattern analysis and machine intelligence (2025).