Proceedings of CONF-CDS 2026 Symposium: Machine Learning and Neural Network Applications in Engineering
DOI: 10.54254/2755-2721/2026.AST37315

Using Statistical Reliability Models to Predict Mechanical Equipment Failures

Shicheng Fang

QSI International School of Haiphong, Haiphong, Vietnam
yydsfsc@163.com

Abstract. Today's engineering systems often experience mechanical equipment failures that result in significant economic losses, production downtime, and safety issues. As a result, the prediction of equipment failure is a crucial research area in engineering and data science. This paper explores the potential of statistical reliability models for estimating failure probability and failure timing for mechanical equipment. The study is based on statistical techniques such as exponential distributions, probability density functions, cumulative distribution functions, expected values, and variance analysis. The paper addresses the following research question: Can statistical modelling be used to predict mechanical equipment failure and enhance maintenance strategies? The study reviews previous research in reliability engineering, predictive maintenance, and statistical failure prediction. The findings show that statistical reliability models can provide engineers with useful methods for predicting equipment lifetime, reducing maintenance costs, and improving system safety. However, conventional statistical models have several limitations, including assumptions of fixed probability distributions, difficulty in modelling complex and nonlinear failure patterns, and limited ability to use large amounts of real-time sensor data. Future research should combine statistical reliability analysis with machine learning, real-time condition monitoring, and Industry 4.0 technologies to improve failure prediction accuracy and support more effective predictive maintenance.

Keywords: Reliability Engineering, Statistical Models, Mechanical Failure Prediction, Exponential Distribution, Predictive Maintenance

1. Introduction

Mechanical equipment plays a crucial role in modern industries, including manufacturing, transportation, energy production, and communication systems. Unexpected failures of mechanical systems may cause financial losses, production delays, and safety hazards [1]. Therefore, accurately predicting equipment failures has become one of the major challenges in reliability engineering.

In recent decades, statistical methods have been widely applied to reliability analysis and predictive maintenance. Traditional approaches, such as exponential distributions, survival analysis, and probability models, have provided engineers with useful tools for estimating equipment lifetime and failure probability [2]. Recent studies have also combined statistical techniques with machine learning and data-driven methods to improve prediction accuracy [3].

© 2026 The Authors. This is an open access article distributed under the terms of the Creative Commons Attribution License 4.0 (https://creativecommons.org/licenses/by/4.0/).

DOI: 10.54254/2755-2721/2026.AST37315

This paper focuses on the application of statistical reliability models in predicting mechanical equipment failures. The main methods discussed in this study include probability density functions, cumulative distribution functions, expected values, and variance analysis [4]. The central research question is whether statistical models can effectively estimate failure probability and support maintenance decision-making in engineering systems.

The value of this research is that it offers a statistical view of mechanical failure prediction and decision-making for maintenance. This paper presents an overview of some of the statistical reliability methodologies available and evaluates their benefits for the engineer to estimate the likelihood of equipment failure, schedule maintenance activities and increase system reliability. This study also addresses the challenges of conventional statistical modelling of complex and data-rich engineering systems. It also covers the possibility of using statistical reliability techniques together with machine learning and Industry 4.0 technologies. The overall goal of this research is to help deepen the understanding of the use of statistical methods to improve mechanical failure prediction and predictive maintenance.

2. Statistical foundations of mechanical reliability

2.1. Failure-time probability and hazard

Suppose that the operating time T of a mechanical component until its first failure is a random variable. The probability density function f(t) is a function that shows how failure probability changes with time, and the cumulative distribution function F(t) is the probability that failure has occurred by time t. The probability that a component will still function after t, known as the reliability function or survival function, is denoted as R(t) [4].

$$R(t) = P(T > t) = 1 - F(t) \tag{1}$$

The sum of the reliabilities and the cumulative failure probability must be equal for the same component in the same failure definition over the same observation period. The density function is the rate of change of F(t), while the hazard function is the intensity of failure at time t given that the subject has survived up to time t. Hazard is not a probability, it has units of inverse operating time, unlike cumulative probability.

$$h(t) = f(t) / R(t) \tag{2}$$

Expected lifetime represents the average length of time in a modelled population, while variance represents how spread out the population is from the average. Both quantities are lifetime distribution dependent. A single average value is not sufficient to indicate that failures are concentrated or widely distributed or that they are more likely to occur as components get older. Thus, effective decisions for maintenance will need to rely on the interpretation of reliability, hazard and uncertainty. Finally, any useful model needs to be able to accurately predict the event it models. Even if the same physical asset is involved, there are different endpoints, such as complete functional shutdown, vibration above safety limit and maintenance when triggered by inspection. When machines run part-time, calendar time and operating hours are not synonymous either. Inconsistencies in the definition of events or exposure measurements can lead to apparent differences in reliability, as this is related to recording practices instead of real mechanical behavior.

DOI: 10.54254/2755-2721/2026.AST37315

2.2. Censoring and operating-condition effects

Industrial reliability records do not usually include a complete failure time for each component. Other machines operate and are monitored until failure occurs or are replaced preventively without failure. The observations are right censored since the failure times are longer than the observed operating times. If censored observations are treated as "failed" or "complete failures" in the analysis, they can lead to biased estimates of lifetime and overly conservative maintenance plans. The Kaplan-Meier estimator takes into account right-censored observations but does not assume any lifetime distribution. The estimated survival probability is updated at each failure time observed using the number of failures and number of components at risk. This can be helpful in describing the empirical reliability if a parametric distribution is not yet warranted [5].

$$S(t) = \prod(1 - d_i / n_i),\ t_i \leq t \tag{3}$$

Failure risk may also change due to operating temperature, vibration, loading, and environment. These covariates are included in the Cox proportional-hazards model, but the baseline hazard is not specified. It is useful under the proportional-hazards assumption and if the operating conditions are measured properly [6]. Therefore, the rules for failure (or not failure), observation windows, missing measurements, and maintenance interventions should be recorded prior to the fitting of any model.

$$h(t \mid x) = h_0(t) \exp(\beta x) \tag{4}$$

Censoring is not necessarily benign. The usual survival estimators all make the assumption of independence of censoring after accounting for relevant information. It becomes problematic when those most in need of replacement are systematically taken out due to vibration problems. Under these conditions, intervention records and condition measurements will be required to explain the end of observation. Reliable analysis should be able to include failures that occurred in the equipment as well as incomplete operating histories without discarding equipment that is still in operation.

3. Parametric failure prediction and maintenance planning

3.1. Exponential reliability model

When failures occur at a more-or-less constant rate, the exponential distribution offers a simple point of departure. The parameter λ is the average number of failures per time of operation. The survival and cumulative distribution functions are closed form and the corresponding density function is f(t) = lambda exp(-lambda t).

$$R(t) = \exp(-\lambda t),\ F(t) = 1 - \exp(-\lambda t) \tag{5}$$

This model assumes that the hazard does not change with the age of the components. The expected lifetime is equal to the reciprocal of its failure rate and the variance of its lifetime is equal to the reciprocal of the failure rate squared. The relationships are useful for initial planning, parts inventory and comparisons of similar operating conditions.

$$E[T] = 1 / \lambda,\ Var(T) = 1 / \lambda^2 \tag{6}$$

DOI: 10.54254/2755-2721/2026.AST37315

If failures are experienced due to unknown external events, a constant hazard can be a good approximation of the useful-life phase of some systems. However, this is not indicative of early manufacturing problems or progressive wear. The exponential distribution is also memoryless: If it has survived to the present, the distribution of the remaining life has the same form. If replacement restores an identical component, and all conditions are equal, then the failure risk will not be reduced even with age-based preventive replacement. A key challenge for machine prognostics is thus to distinguish mathematically convenient assumptions from physically credible degradation mechanisms [7]. The estimated rate only applies to a specific operating population and to a specific time of exposure. A mix of machines may have a workload, maintenance history or machine description that doesn't reflect the average of all the individual groups. If a constant-hazard model is adopted, then the survival pattern should be compared to the reality and adjusted accordingly if the operating conditions change. The main difference between it and physical realism is that it is translatable versus being realistic across the board.

3.2. Weibull reliability model

The Weibull distribution generalizes reliability analysis by enabling failure intensity with operating time to be decreasing, constant, or increasing. Its scale parameter eta sets its characteristic life time, and its shape parameter beta sets the direction and the strength of aging. This flexibility allows the model to be used for comparison with different mechanical failure mechanisms [4].

$$R(t) = \exp[-(t/\eta) \hat{} \beta] \tag{7}$$

$$h(t) = (\beta/\eta)(t/\eta) \hat{} (\beta - 1) \tag{8}$$

If beta is less than one, the hazard will decrease in time, and may indicate early failures. If β=1 then the Weibull distribution becomes the exponential distribution with a constant hazard rate. If beta is greater than 1, the hazard increases with age and is consistent with progressive fatigue, corrosion or wear under the right operating conditions.

Flexibility does not imply automatic validity of a model. Well-defined failure data, for example, exposure times and accounting for censoring are essential for parameter estimation. Distribution selection should be made based on mechanical knowledge as a single curve may represent multiple competitive failure mechanisms. The comparison in Figure 1 shows two hypothetical survival curves with a similar characteristic timescale, with the difference that one assumes a constant hazard level, while the other assumes that the hazard level increases as the curve progresses.

The characteristic lifetime is not the same as the arithmetic mean lifetime and is not the lifetime of a typical failure. The survival function at t=eta is always exp(-1)=0.3679 (for any shape parameter). The mean value, however, depends jointly on the scale and shape parameters via the gamma function. This distinction is important when communicating maintenance thresholds since a similar characteristic lifetime may be associated with different early life and wear-out behavior.

DOI: 10.54254/2755-2721/2026.AST37315



Figure 1. Illustrative exponential and Weibull reliability curves

3.3. Hypothetical numerical demonstration

The exponential model is represented by a hypothetical failure rate of 0.001 failures per operating hour. This value is chosen just for purposes of explanation and is not estimated from an observed machine, experiment or proprietary data. The expected lifetime is assumed to be 1,000 operating hours and the variance 1,000,000 (squared hours). The probabilities of survival and failure for selected operating durations are calculated and presented in Table 1.

Table 1. Illustrative exponential survival and failure probabilities

Operating time (h)	Reliability R(t)	Failure probability F(t)	Assumed constant hazard
250	0.7788	0.2212	0.001 / hour
500	0.6065	0.3935	0.001 / hour
750	0.4724	0.5276	0.001 / hour
1,000	0.3679	0.6321	0.001 / hour
1,500	0.2231	0.7769	0.001 / hour
2,000	0.1353	0.8647	0.001 / hour

After 500 hours, the model gives R(500) = exp(-0.5) = 0.6065 and F(500) = 0.3935. After 1000 hours, the reliability drops to 0.3679 and the cumulative failure probability to 0.6321. These are the values that represent a population of components and do not predict the actual failure time of any one component.

The exponential survival equation can be used to solve for the inspection time if a minimum reliability threshold is given. The threshold for a desired survival probability of 0.80 is about 223 operating hours. The same threshold would happen after about 472 hours for the illustrative Weibull curve having an eta of 1000 hours and a beta of 2. The difference is not a reflection of better performance of the models in practice but of their different hazard assumptions.

$$t = -\ln(R^*)/\lambda \tag{9}$$

An inspection threshold is NOT the same as an optimized replacement policy. The actual decisions will have to take into account the consequences of downtime, the cost of intervening, the

DOI: 10.54254/2755-2721/2026.AST37315

criticality of the component, the evidence from the sensors, the effectiveness of the inspection, and the uncertainty of the parameter. For a strictly memoryless exponential component, the modeled future hazard can be shown to be no better through routine replacement than simply monitoring and risk-based inspection.

The chosen threshold is also an administrative risk criterion and not a safety boundary found in a laboratory setting. Different levels of intervention may be warranted given the difference in consequences of failure: A critical turbine, a redundant conveyor motor and a low-cost replaceable pump may merit different levels of intervention. The range of plausible inspection times would be further expanded if there is parameter uncertainty. A practical implementation should therefore be a mix of probability estimates, as well as documented safety requirements, capacity for maintenance, and the consequences of failure to maintain as well as the consequences of unnecessary maintenance.

4. Comparative evaluation and future directions

4.1. Model selection and statistical limitations

There is no universal reliability model that can be used for all mechanical systems. The simplicity of exponential models, the ability of Weibull models to represent some aging patterns, the summarization of censored survival observations using Kaplan-Meier models, and the evaluation of measured operating conditions through Cox regression models are all strong features of these models. In Table 2, the approaches are compared on the basis of the following assumptions and limitations:

Table 2. Comparison of reliability and survival-analysis methods

Method	Hazard or survival assumption	Primary application	Key limitation
Exponential	Constant hazard	Simple failure-risk baseline	Cannot represent aging
Weibull	Decreasing, constant, or increasing hazard	Failure-pattern and wear analysis	Distribution and parameter sensitivity
Kaplan-Meier	No fixed survival distribution	Right-censored survival description	Limited direct covariate interpretation
Cox regression	Proportional hazard ratios	Risk associated with operating conditions	Assumption and covariate-quality dependence

Model selection should consider failure mechanisms, the amount of samples, the quality of observation, and the decision to be made during maintenance. Poor distributional assumptions can be detected by visual inspection of survival curves, residual analysis, uncertainty intervals and external validation. Additional methods such as left truncation, recurrent failure, competing risks, and informative censoring may be needed where the topics in this introduction are not applicable.

When a model looks mathematically sound, the small samples and infrequent failures yield ambiguous estimates of the parameters. Historical relationships are also likely to be unstable if there is a change in maintenance practice or operating environment. Thus, the results of the prediction

DOI: 10.54254/2755-2721/2026.AST37315

must be accompanied by the assumptions underlying the prediction, and the result must be revised as new operational evidence is gathered.

Repairable equipment is another distinction between the lifetime of a replaceable unit and the sequence of failures of a maintained system. The repair can either bring the system back to almost as good as new or have an intermediate effect or leave it the same. If the failure is not correlated to other failures and it is not assessed for the effectiveness of its maintenance operations, then every post-repair period may be treated as a failure-free period, which can lead to a misstatement of failure risk. Reliability predictions must be converted to operational policy after reporting of system boundaries and repair assumptions.

4.2. Integration with machine learning

When equipment provides high-dimensional data on condition monitoring, machine-learning techniques can be used in addition to reliability models. Nonlinear degradation patterns may be present in the vibration spectra, temperature histories, acoustic measurements and electrical signals and cannot be described by a single lifetime distribution. Predictive maintenance applications using decision trees, neural networks, support-vector methods, and other learning algorithms are discussed in reviews [8].

But predictive complexity does not equate with reliable deployment. Class imbalance occurs as a result of rare failure events, and maintenance interventions can cause failure labels to be unobserved during future events. However, random split of data can also lead to false conclusions if measurements from the same machine are included in the training and evaluation sets. Time-aware validation, asset-based separation, calibrated probabilities, and explicit uncertainty assessment are therefore critical, protective features.

Statistically interpretable survival relationships can be synthesized with sensor-derived health indicators—hybrid approaches. Examples of this include machine-learning aspects that can be used as inputs to a survival-regression model, or the model-based failure probabilities that can be used to prioritize maintenance. Claimed improvements should be backed up with held-out data and/or operational evaluative criteria that are representative, not assumed from algorithm complexity.

Even though interpretability is necessary, the reason is because a maintenance recommendation has an impact on safety, labor allocation, and production planning. A model comprising an alert about an increased risk should include the measurements contributing to the alert, the prediction time horizon and an indicator of whether the observation is out of the range of conditions the model was trained for. Once a model is implemented, with its additional uncertainty and cost, statistical baselines can serve a valuable reference for assessing if the more complex model shows meaningful improvement.

4.3. Industry 4.0 and real-time monitoring

Industry 4.0 is a fusion of the physical, the sensor, the communication and the analysis. This movement from equipment-level measurements to information processing and decision support in adaptive maintenance is built on the operational foundation of cyber-physical architectures [9]. Routine monitoring can be used to record the changes of covariates, detect abnormal behavior, and assist in the reevaluation of equipment risk with changing conditions.

Such advantages rely on reliable data governance, working out-of-sync timestamps, sensor calibration, cybersecurity and maintenance-management system integration. The analytical methods, organizational process, and implementation infrastructure are all essential elements that need to be

DOI: 10.54254/2755-2721/2026.AST37315

taken into consideration when talking about the application of Industry 4.0 maintenance [10]. Future research should assess the hybrid models on transparent industrial datasets while reporting uncertainties and comparing maintenance outcomes not only by classification accuracy.

The successful deployment also relies on a feedback system from completed maintenance to the analytical records. The results of inspections, replaced parts and verified failures should be associated with the sensor history and operating interruptions. If there is no traceability, an apparently sophisticated monitoring system can collect data, but provide little reliable information on equipment deterioration.

5. Conclusion

The statistical reliability models offer a consistent approach to convert the uncertainties associated with equipment life into more meaningful concepts of survivability, failure probability, hazard and expected operating time. The analysis shows that these quantities can be used for inspection planning and maintenance prioritization if the model assumptions hold true for the component and the operating conditions. The hazard rate is constant and the expected lifetime is the reciprocal of the failure rate in the exponential model; the calculations are particularly easy in this case. The calculated reliability would be 0.6065 at 500 operating hours and 0.3679 at 1,000 operating hours, assuming the failure rate is 0.001 failures per operating hour. These values are mathematical illustrations, not experimental data or evidence of successful predictions. The model's memoryless property also does not allow for improving the assumed future hazard by itself if using age-based replacement.

The Weibull distribution has the flexibility to represent decreasing, constant or increasing failure intensity. The estimation of the right-censored observations did not assume any particular lifetime distribution, and Cox regression correlated the risk of equipment failure to the observed operating conditions. Among these approaches, one needs to pay attention to physical degradation mechanisms, censoring, data quality, sample size and uncertainty.

Several limitations still remain. The study is not an experimental study but a conceptual literature-based study that does not contain measured failure histories, independently estimated parameters or results of predictive validation. So, there's no empirical superiority to any model. Future studies should provide representative sets of equipment data, maintain and store maintenance and censoring data, compare models by suitable temporal validation and analyze models at the decision level (downtime and maintenance cost). A combination of transparent reliability models, condition-monitoring signals, machine-learning characteristics, and cyber-physical infrastructure represents a promising way forward—but improvements need to be backed by convincing operational evidence.

References

[1] Jardine, A. K. S., Lin, D., & Banjevic, D. (2006). A review on machinery diagnostics and prognostics implementing condition-based maintenance. *Mechanical Systems and Signal Processing, 20*(7), 1483–1510.

[2] Zio, E. (2009). Reliability engineering: Old problems and new challenges. *Reliability Engineering and System Safety, 94*(2), 125–141.

[3] Si, X. S., Wang, W., Hu, C. H., & Zhou, D. H. (2011). Remaining useful life estimation: A review on the statistical data driven approaches. *European Journal of Operational Research, 213*(1), 1–14.

[4] Meeker, W. Q., Escobar, L. A., & Pascual, F. G. (2021). *Statistical methods for reliability data* (2nd ed.). John Wiley and Sons.

[5] Kaplan, E. L., & Meier, P. (1958). Nonparametric estimation from incomplete observations. *Journal of the American Statistical Association, 53*(282), 457–481.

DOI: 10.54254/2755-2721/2026.AST37315

[6] Cox, D. R. (1972). Regression models and life-tables. *Journal of the Royal Statistical Society: Series B (Methodological), 34*(2), 187–220.
[7] Peng, Y., Dong, M., & Zuo, M. J. (2010). Current status of machine prognostics in condition-based maintenance: A review. *The International Journal of Advanced Manufacturing Technology, 50*(1-4), 297–313.
[8] Carvalho, T. P., Soares, et al. (2019). A systematic literature review of machine learning methods applied to predictive maintenance. *Computers and Industrial Engineering, 137*, 106024.
[9] Lee, J., Bagheri, B., & Kao, H. A. (2015). A cyber-physical systems architecture for Industry 4.0-based manufacturing systems. *Manufacturing Letters, 3*, 18–23.
[10] Zonta, T., da Costa, et al. (2020). Predictive maintenance in the Industry 4.0: A systematic literature review. *Computers and Industrial Engineering, 150*, 106889.